


—	۵	بر	m	O







LAYOUT SHOWN AS

Keying Shown as example

CHARACTERISTICS

ယ

 \sim

-Mass

BASIC SERIES:

SHELL SIZE : 11

PLATING : S = Nickel

Н

SHELL TYPE : Square Flange Receptacle

CONTACT TYPE : Standard Crimp Contact

-Standard : Based on MIL-DTL-38999 Series III

-Shell Material : Stainless Steel -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy : Silicon Elastomer -Seals & Grommet -Contact Plating : Gold over copper Alloy 0.8µm minimum -Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories : -65°C to +200°C -Temperature Range -Salt Spray : 500 hours

: 32.47 g ± 10%

8D 0

G

11

S

01

В


F

D

Connector	Connector dimension		
Dim	Nominal		
Р	3.25±0.2		
PP	4.93±0.2		
R1	20.62		
R2	18.26		
S	26.2±0.3		
V	20.83+0/-1.25		
W	2.1/2.5		
Z	31.5 Max		
VV THREAD	M15x1-6g		

Е

SOURIAU shall not be liable for due to a use of the Products the Specifications issued by either (professional recomment



	ω		A		
	R				4
S EXA	AMPLE				3
s which er of t indation untry R	non-conformit ch does not co he Parties or b on, technical no Jurisd	mply with by a third part			2
					-
		CUSTOME		MOD N°	
Stee	CUSTOMER DRAWING Steel Receptacle 8D series				
ar			PROJECT 59		1
I.CC	.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission				
	DRG N° 1BD-C			SHEET 1/2	
	B		A		J

r	T	۵	г – – – – – – – – – – – – – – – – – – –	m	D	0
		Contact Layout				Panel Cutout
4	(01			22	SQUARE FLANGE RECEPTACLE (TYPE 0) REAR MOUNTING
	Ctc A	1#12 11-01 X Y 0 0			<u>v</u>	Dim
ω			J			ØA ØAA R1 ØT
						SOURIAU shall not be liable for any due to a use of the Products whi the Specifications issued by either of (professional recommendation)
N					A 07-10-202	Country FR PN: 8D011S
					ISS DATE Designed By: TITLE	Latest modification - by Date: Stainless Ste
_					SCALE NA	General linear Tolerances: ±
					FORMAT A3	J WWW.SOURIAU.Co SOURIAU 8D011S0
L	Н	G	F	E	D	С

