



These are full length hollow shaft nut drivers intended for working with long bolts. They are designed with cushion gripped ergonomic color coded handles. Handles provide greater torque and user comfort. Overall length 7".

| SPECIFICATIONS              | ND-301132                | ND-63012                 | ND-63014                 | ND-630316                | ND-63038                 | ND-630516                | ND-630716                | ND-630916                | ND-631   | ND-SET4                   |
|-----------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--|---------------------------|
| <b>DRIVER SIZE</b>          | 11/32"<br>(8.73mm)       | 1/2"<br>(12.7mm)         | 1/4"<br>(6.35mm)         | 3/16"<br>(4.763mm)       | 3/8"<br>(9.53mm)         | 5/16"<br>(7.94mm)        | 7/16"<br>(11.11mm)       | 9/16"<br>(14.29 mm)      | 3/16" 1/4"<br>5/16" 11/32"<br>3/8" 7/16"<br>1/2" | 5/16" 11/32"<br>3/8" 1/2" |
| <b>SHAFT MATERIAL</b>       | Chrome Vanadium Steel    | Chrome Vanadium Steel    | Chrome Vanadium Steel    | Chrome Vanadium Steel    | Chrome Vanadium Steel    | Chrome Vanadium Steel    | Chrome Vanadium Steel    | Chrome Vanadium Steel    | Chrome Vanadium Steel                            | Chrome Vanadium Steel     |
| <b>HANDLE</b>               | Ergonomic Cushion Grip   | Ergonomic Cushion Grip   | Ergonomic Cushion Grip   | Ergonomic Cushion Grip   | Ergonomic Cushion Grip   | Ergonomic Cushion Grip   | Ergonomic Cushion Grip   | Ergonomic Cushion Grip   | Ergonomic Cushion Grip                           | Ergonomic Cushion Grip    |
| <b>HANDLE GRIP MATERIAL</b> | TPR Thermoplastic Rubber | TPR Thermoplastic Rubber | TPR Thermoplastic Rubber | TPR Thermoplastic Rubber | TPR Thermoplastic Rubber | TPR Thermoplastic Rubber | TPR Thermoplastic Rubber | TPR Thermoplastic Rubber | TPR Thermoplastic Rubber                         | TPR Thermoplastic Rubber  |
| <b>STANDARDS</b>            | ASME B107 110/ANSI       | ASME B107 110/ANSI       | ASME B107 110/ANSI       | ASME B107 110/ANSI       | ASME B107 110/ANSI       | ASME B107 110/ANSI       | ASME B107 110/ANSI       | ASME B107 110/ANSI       | ASME B107 110/ANSI                               | ASME B107 110/ANSI        |
| <b>SHAFT LENGTH</b>         | 3" (76.2 mm)             | 3" (76.2 mm)             | 3" (76.2 mm)             | 3" (76.2 mm)             | 3" (76.2 mm)             | 3" (76.2 mm)             | 3" (76.2 mm)             | 3" (76.2 mm)             | 3" (76.2 mm)                                     | 3" (76.2 mm)              |
| <b>HOLLOW DEPTH</b>         | 6.75"                    | 6.75"                    | 6.75"                    | 6.75"                    | 6.75"                    | 6.75"                    | 6.75"                    | 4"                       | 6.75"  | 6.75"                     |
| <b>OVERALL LENGTH</b>       | 7"                       | 7"                       | 7"                       | 7"                       | 7"                       | 7"                       | 7"                       | 7"                       | 7"   | 7"                        |
| <b>WEIGHT</b>               | 0.35 lbs<br>(158.76g)    | 0.343 lbs<br>(155.59g)   | 0.318 lbs<br>(144.24g)   | 0.319 lbs<br>(144.70g)   | 0.35 lbs<br>(158.76g)    | 0.333 lbs<br>(151.05g)   | 0.357 lbs<br>(161.93g)   | 0.29 lb<br>(131.66 g)    | 2.213 lbs<br>(1,0038kg)                          | 2.609 lbs<br>(1,183kg)    |
| <b>UPC #</b>                | 811490012110             | 811490012059             | 811490012066             | 811490012073             | 811490012080             | 811490012097             | 811490012103             | 810053352076             | 811490010819                                     | 811490015784              |

