



Main

| | |
|-----------------------------|---|
| Range | Spacial |
| Product name | Spacial S3D |
| Application | Multi-purpose |
| Category | Compact enclosure |
| Enclosure nominal height | 39.37 in (1000 mm) |
| Enclosure nominal width | 31.50 in (800 mm) |
| Enclosure nominal depth | 15.75 in (400 mm) |
| Door type | Glass |
| Mounting plate description | Without mounting plate |
| Type of gland plate | Standard |
| Installation accessory type | Wall-mounting |
| Device composition | 1 body 2 cable gland plate 1 door 1 lock |

Complementary

| | |
|-----------------------------|--|
| Body type | Single piece body Gutter-shaped front rail double sheet thickness |
| Number of doors | Front face 1 |
| Door opening side | Reversible 120 °) |
| Lock type | 3 points lock, 3 mm double-bar |
| Accessibility for operation | Front |
| Removable parts | Door by hinges Cable gland plate by screws |
| Material | Body steel Door steel and security glass |
| Surface finish | Epoxy-polyester powder |
| Color | Gray RAL 7035) |
| Standards | IEC 62208 |
| Product Certifications | UL DNV GL LR CUL BV |
| Net Weight | 90.39 lb(US) (41 kg) |

Environment

| | |
|-------------------------------|-------------------------------------|
| Electromagnetic compatibility | Electromagnetic field immunity test |
| NEMA Degree of Protection | NEMA 4X/13 |
| IK degree of protection | IK08 IEC 62262 |
| IP degree of protection | IP66 IEC 60529 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ordering and shipping details

| | |
|-----------------------|--|
| Category | 80034-ENCLOSURE SYSTEMS WALL MOUNT METAL |
| Discount Schedule | ES1 |
| GTIN | 3606480160073 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 88.18 lb(US) (40.0 kg) |
| Returnability | No |
| Country of origin | FR |

Packing Units

| | |
|------------------------------|--------------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 17.72 in (45.0 cm) |
| Package 1 width | 32.28 in (82.0 cm) |
| Package 1 Length | 40.55 in (103.0 cm) |
| Unit Type of Package 2 | PAM |
| Number of Units in Package 2 | 4 |
| Package 2 Weight | 390.22 lb(US) (177.0 kg) |
| Package 2 Height | 70.08 in (178.0 cm) |
| Package 2 width | 39.37 in (100.0 cm) |
| Package 2 Length | 47.24 in (120.0 cm) |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|