


Product data sheet

Specifications



Internal door for Spacial WM
encl.H1000xW800 steel,
RAL7035.Adjustable in depth

NSYPIN108

Main

Range	Spacial
Accessory / separate part category	Enclosure accessory
Product or component type	Door
Application	Multi-purpose
For enclosure nominal dimensions	-
Mounting location	Step slide Front side
Range compatibility	Spacial (Spacial CRN) Spacial (Spacial S3D) Spacial (Spacial S3X)
Device composition	1 door 4 fixing brackets 2 mounting uprights

Complementary

Material	Door: sheet steel
Colour	All faces: grey (RAL 7035)
Surface finish	Polyester powder
Lock type	Lock 3 mm double bar
Number of locks	1
Adjustment	Pitch 25 mm (on step slides)
Door type	Internal plain
Door opening side	Reversible
Maximum load	30 kg/m ²
Height	1000 mm nominal:
Width	800 mm nominal:
Product weight	10 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Height	4.500 cm
Package 1 Width	75.500 cm
Package 1 Length	96.500 cm
Package 1 Weight	12.712 kg
Unit Type of Package 2	P12
Number of Units in Package 2	15
Package 2 Height	90.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	202.680 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)