



In case of consideration for using Autom otive equipm ent/device which dem and high re liability, kindly contactour sales w indow correspondents.

APPLICABLE STANDARD		TEST METHOD		REQUIREMENTS		Q/T	AT
OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C ⁽¹⁾	STORAGE TEMPERATURE RANGE	-10 °C TO 60 °C ⁽²⁾			×	×
VOLTAGE	200 V AC	OPERATING HUMIDITY RANGE	40 % TO 80 %			×	×
CURRENT	1 A	STORAGE HUMIDITY RANGE	40 % TO 70 % ⁽²⁾			×	×
SPECIFICATIONS							
ITEM	TEST METHOD		REQUIREMENTS		Q/T	AT	
CONSTRUCTION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.		×	×
MARKING		CONFIRMED VISUALLY.				×	×
ELECTRIC CHARACTERISTICS							
CONTACT RESISTANCE	100 mA (DC OR 1000 Hz).	15 m Ω MAX.				×	-
INSULATION RESISTANCE	500 V DC	1000 M Ω MIN.				×	-
VOLTAGE PROOF	650 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.				×	-
MECHANICAL CHARACTERISTICS							
CONTACT INSERTION AND EXTRACTION FORCES	\square 0.5 \pm 0.002mm BY STEEL GAUGE.	INSERTION FORCE: 2.45 N MAX. EXTRACTION FORCE: 0.25 N MIN.				×	-
MECHANICAL OPERATION	100 TIMES INSERTIONS AND EXTRACTIONS.	①CONTACT RESISTANCE: 20 m Ω MAX. ②NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				×	-
VIBRATION	FREQUENCY 10 TO 55 Hz. AMPLITUDE : 1.5 mm, AT 2h FOR 3 DIRECTIONS.	①NO ELECTRICAL DISCONTINUITY OF 1 μ s. ②NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				×	-
SHOCK	490 ms ² , DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.					×	-
ENVIRONMENTAL CHARACTERISTICS							
DAMP HEAT (STEADY STATE)	EXPOSED AT 40 \pm 2 °C, 90 ~ 95 %, 96 h.	①CONTACT RESISTANCE: 20 m Ω MAX. ②INSULATION RESISTANCE: 1000 M Ω MIN.				×	-
RAPID CHANGE OF TEMPERATURE	TEMPERATURE: -65 \rightarrow +15 \sim +35 \rightarrow +125 \rightarrow +15 \sim +35 °C TIME 30 \rightarrow 10 \sim 15 \rightarrow 30 \rightarrow 10 \sim 15 min. UNDER 5 CYCLES.	③NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				×	-
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.	①CONTACT RESISTANCE: 20 m Ω MAX. ②NO HEAVY CORROSION.				×	-
SULPHUR DIOXIDE	EXPOSED IN 10 PPM FOR 96 h. (TEST STANDARD: JEIDA - 39)					×	-
RESISTANCE TO SOLDERING HEAT	1) SOLDER BATH: SOLDER TEMPERATURE, 260 \pm 5 °C. FOR IMMERSION DURATION, 10 \pm 1 s. 2) SOLDERING IRONS : 350 °C FOR 3 s MAX.	NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.				×	-
SOLDERABILITY	SOLDERED AT SOLDER TEMPERATURE, 245 \pm 3 °C, FOR IMMERSION DURATION, 2 s.	A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSERD.				×	-
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE			
							
REMARK ⁽¹⁾ TEMPERATURE RISE INCLUDED WHEN ENERGIZED. ⁽²⁾ THIS STORAGE INDICATES A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE THE BOARD MOUNTED.							
Unless otherwise specified, refer to MIL-STD-1344.							
Note Q/T: Qualification Test A/T: Assurance Test X: Applicable Test		DRAWING NO.		ELG4-081233-21			
HRS		SPECIFICATION SHEET		PART NO.	A3C-16DA-2DSA (71)		
		HIROSE ELECTRIC CO., LTD.		CODE NO.	CL621-0507-2-71		
					 1/1		