

HDC enclosures HDC 24D TOBO 1PG29G

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General ordering data

Order No.	1654920000
Type	HDC 24D TOBO 1PG29G
Version	HDC enclosures, Size: 4, Protection degree: IP 65, Cable entry from top, Plug housing, Side-locking clamp on upper side, high, Size of cable entries: PG 29
GTIN (EAN)	4008190407926
Qty.	1 pc(s).

HDC enclosures HDC 24D TOBO 1PG29G

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Dimensions and weights

Length	110.5 mm	Width	55 mm
Height	72 mm	Net weight	245 g

Dimensions

Total length housing	73 mm	Width housing C	43 mm
Height of housing B	72 mm	Cable entry	w. threading

General data

Housing main material	diecast aluminium
-----------------------	-------------------

Version

Design of housing	Cable entry from top, Plug housing	Size	4
Design	high	Top part/bottom part/lid	upper part
Design of locking system	Side-locking clamp on upper side	Cable entry	w. threading
Size of cable entries	PG 29	Number of cable entry on top	1
Number of cable entry sideways	0		

Classifications

ETIM 2.0	EC000437	ETIM 3.0	EC000437
UNSPSC	30-21-18-01	eClass 4.1	27-14-08-05
eClass 5.1	27-14-34-19	eClass 6.2	27-26-12-03
eClass 7.1	27-44-02-02		

Approvals

ROHS	Conform
------	---------

Downloads

PDF	1654920000_HDC_24D_TOBO_1PG29G_STP_Blatt_1.pdf
IGES	1654920000_HDC_24D_TOBO_1PG29G_STP.igs
VRML	1654920000_HDC_24D_TOBO_1PG29G_STP.wrl
EPLAN	1654920000.MZF
	3-D model

Data sheet...

**HDC enclosures
HDC 24D TOBO 1PG29G**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

