



DESIGNED FOR USE WITH	
RG-188/U	
CABLE ENTRY DIAMETER	
MINIMUM	
COLLAR	.066
CLAMP NUT	.112

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 ₃	REVISED	DAC 6/15/99	DCM 6/16/99

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Nominal Impedance (Ohms) <u>50</u>	Interface Dimensions MIL-STD-348A, Fig. 310.1	Temperature Rating <u>-60°C to +165°C</u>
Frequency Range (GHz) DC to <u>12.4</u>	Recommended Mating	Vibration MIL-STD-202, Method 204, Condition D.
Volt Rating (VRMS MAX)	Torque <u>7 - 10 in-lbs</u>	Shock MIL-STD-202, Method 213, Condition I.
@ Sea Level <u>250</u>	Mating Characteristics:	Thermal Shock MIL-STD-202, Method 107, Condition B.
VSWR <u>1.15 + .01</u>	Insertion (MAX Lbs) <u>N/A</u>	Except High Temp shall be +85°C
Insertion Loss (dB MAX) <u>.08 √f(GHz)</u>	Withdrawal (MIN Oz) <u>N/A</u>	Moisture Resistance MIL-STD-202, Method 106
RF Leakage (dB MIN) <u>-[60-f(GHz)]</u>	Force to Engage and Disengage (In-Lbs MAX) <u>2.0</u>	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray
Corona, 70,000 Ft (VRMS MIN) <u>190</u>	Center Contact Captivation	
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level <u>750</u>	Axial (Lbs) <u>6.0</u>	
Contact Resistance (Milliohms MAX)	Radial (In-Oz) <u>4.0</u>	
Center Contact <u>2.0</u>	Cable Retention	
Outer Contact <u>2.0</u>	Axial Force (Lbs) <u>30</u>	
Cable to Housing <u>0.5</u>	Torque (In-Oz) <u>N/A</u>	
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) <u>500</u>	Weight (Grams) <u>TBD</u>	
LR.(Megohms MIN) <u>10,000</u>		

COMPONENT	MATERIAL	FINISH
HOUSING COUPLING NUT CLAMP NUT CAP	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	GOLD PLATE PER MIL-G-45204
CENTER CONTACT COLLAR	BRASS PER ASTM-B-16 HALF HARD	GOLD PLATE PER MIL-G-45204
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
RETAINING RING	BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H	N/A
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON	DRAWN BY	DATE	AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599
	BWC	6-05-67	
FRAC. DEC. ANGLES	CHECKED BY	APPD BY	AMP TITLE OSM RIGHT ANGLE CABLE PLUG CLAMP ATTACHMENT SIZE B CODE IDENT NO. 26805 2007-7188-00 REV 01 ₃ SCALE 5 : 1 SHEET 1 OF 1
± 1/64 ±.005 ± °	D. NANIA	8/31/67	
These drawings and specifications are the property of AMP Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASS'Y PROCEDURE	408-04965 NO. A(20-077)	