

	'art 12188				<u> </u>	DES!	CRIP			n	C <i>P</i>		LENGT .I M	Н													
	12188					I ML A s							. 2 M														
		PIN	CA	LL C	)UT	CHA	RT f	for 1	01218	88-0	01LF	· 			PI	N CA		OUT	CH	ART	for	1012	1888	-002L	LF		
	L	K	J	I	Н	G	F	Е	D	С	В	A			L	K	J	I	Н	G	F	Е	D	С	В	A	
0	G	S	G	S	G	S	G	S	G	S	G	S	1	0	G	S	G	S	G	S	G	S	G	S	G	S	1
X	S	G	S	G	S	G	S	G	S	G	S	G	2	X	S	G	S	G	S	G	S	G	S	G	S	G	2
0	G	S	G	S	G	S	G	S	G	S	G	S	3	0	G	S	G	S	G	S	G	S	G	S	G	S	3
X	S	G	S	G	S	G	S	G	S	G	S	G	4	X	S	G	S	G	S	G	S	G	S	G	S	G	4
0	G	S	G	S	G	S	G	S	G	S	G	S	5	0	G	S	G	S	G	S	G	S	G	S	G	S	5
X	S	G	S	G	S	G	S	G	S	G	S	G	6	Χ	S	G	S	G	S	G	S	G	S	G	S	G	6
0	G	S	G	S	G	S	G	S	G	S	G	S	7	0	G	S	G	S	G	S	G	S	G	S	G	S	7
Χ	S	G	S	G	S	G	S	G	S	G	S	G	8	X	S	G	S	G	S	G	S	G	S	G	S	G	8
0	G	S	G	S	G	S	G	S	G	S	G	S	9	0													ę
X	S	G	S	G	S	G	S	G	S	G	S	G	10	X													10
spec ref tolerance std TOLERANCES UNLESS OTHERWISE SPECIFIED							SS IFD	dr         Jason Gu         2013/07/04           eng         Jason Gu         2013/08/22           chr         -         -						projection N				MN	size A 4			A 4	s c a l e l : 2 ELX-N-15589-1				
	surf	ace \	-/	linea	r (	0.X 0.XX 0.XXX	± ±	<u>E</u>	<b>F</b>	Roger Cher	⊕  +-  +		<b>2013/08/22</b> ARD MAX VS		RCC		ECT	SY		1 1	o m d mad	l	e	2188	88	Rele	r

> I METER TO 10 METER: ±2% OF "DIM LI" > 10 METER: +0 / -4% OF "DIM LI"

2. ALL CABLE ASSEMBLIES SHALL BE TESTED 100% FOR CONTINUITY AS DEFINED IN WIRING LIST.

- 3. UNLESS OTHERWISE SPECIFIED ALL CABLE ASSEMBLIES SHALL BE 100% HI-POT TESTED BY APPLYING 300V DC FOR MINIMUM OF 10ms, UNLESS ACTIVE COMPONENTS ARE USED IN THE ASSEMBLY.
- 4. OTHER TESTING PERFORMED AS REQUIRED BY PRODUCT SPECIFICATION: GS-12-344.
- 5.) THIS DIMENSION IS A FINISHED PRODUCT LENGTH.
- 6. LEAD FREE PRODUCTS MEET EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.
- 7. CONNECTOR ASSEMBLIES SHOWN ARE FOR REFERENCE ONLY AND MAY NOT SHOW ALL PART DETAIL. REFERENCE CONNECTOR ASSEMBLY DRAWINGS FOR COMPLETE DETAILS.
- 8. GLOBAL STANDARDS PER CABLE PACKAGING: GS-14-1093.
- 9. LABEL:
  MANUFACTURER CODE OR NAME
  PART NUMBER
  REVISION
  DATE CODE WW/YY FORMAT
  COUNTRY OF ORIGIN
  FONT SHALL BE CLEARLY VISABLE AND BLACK IN COLOR
- IO. A "\_\_\_\_ SYMBOL WILL BE NEXT TO ANY DIMENSION, VIEW, OR NOTE WHICH HAS BEEN MODIFIED WITH THE CURRENT DRAWING REVISION. THE CURRENT REVISION WILL BE SHOWN IN THE SYMBOL.

spec ref			dr .	Jason Gu		2013/07/04	proje	ection		111	s i z e	scale	
tolerance std	TO. 51		e n g Jason Gu			2013/08/22			MM		A 4	1:2	
	TOLET	RANCES U Wise spe	INLESS ECIFIED	chr -	-		-			-		ecn no	ELX-N-15589-1
	OTTILIN		appr	Roger Cheng		2013/08/22	product	family		-	rel level	Released	
		0.X	土	C	<b>C</b> :	□ RA	ARD INTE	2 C O NI NI [	CT CV	V C T E M	0 =		rev
surface (-/	linear	0.XX	土	「		-  -  -	AND INIL	COMM	_ (   )		$\circ$	101218	88
		0.XXX	土	]		+ AIR	RMAX VS CABLE	E ASSEME	3LY (10	IMLA)	\$ \( \( \) \( \)		С
	angular	0°	±°	www.1	fci.com	cat, no	◊.	-	Pro	duct -	Inspectio	n Drw	sheet 3 of 3

opyright FCL

D

Pro/E File - REV C - 2009-06-09

PDS: Rev :C

STATUS:Released

Printed: Aug 23, 2013