

Product data sheet

Specifications



surge arrester cartridge, Multi9 PRD1 75r, 1P, 240 V

M9LC275

Main

Range of product	Multi9
Product name	Multi9 PRD
Product or component type	Cartridge
Poles description	1P

Complementary

Surge arrester class type	Type 1
Surge arrester technology	MOV
[Ue] rated operational voltage	240 V AC 50...60 Hz
Nominal discharge current	20 kA
Maximum discharge current	75 kA
[Uc] maximum continuous operating voltage	275 V
Maximum [Up] voltage protection level	<900 V
Local signalling	Mechanical indicator (green and red)
Mounting mode	Plug-in
Mounting support	Into SPD module
9 mm pitches	2
Height	45 mm
Width	17.5 mm
Depth	68.5 mm
Product weight	82 g
Colour	Grey (RAL 7035)
Response time	< 25 ns

Environment

Standards	UL 1449
Quality labels	CSA UR
IP degree of protection	NEMA 1

Relative humidity	0...95 %
Operating altitude	0...2000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.5 cm
Package 1 Width	7.8 cm
Package 1 Length	10.5 cm
Package 1 Weight	76 g
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	1.2 kg

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Recommended replacement(s)