

# FAN73611

## Single-Channel High-Side Gate Drive IC

### Features

- Floating Channel for Bootstrap Operation to +600V
- 250mA/500mA Sourcing/Sinking Current Driving Capability
- Common-Mode dv/dt Noise-Canceling Circuit
- 3.3V and 5V Input Logic Compatible
- Output In Phase with Input Signal
- Under-Voltage Lockout for  $V_{DD}$  and  $V_{BS}$
- 8-Lead Small Outline Package (SOP)

### Applications

- High-Speed Gate Driver
- Plasma Display Panel
- Switching-Mode Power Supply (SMPS)
- Motor Drive Inverter

### Description

The FAN73611 is a monolithic high-side gate drive IC that can drive MOSFETs and IGBTs operating up to +600V. Fairchild's high-voltage process and common-mode noise canceling techniques provide stable operation of the high-side driver under high dv/dt noise circumstances. An advanced level-shift circuit offers high-side gate driver operation up to  $V_S=9.8V$  (typical) for  $V_{BS}=15V$ . The UVLO circuits prevents malfunction when  $V_{DD}$  or  $V_{BS}$  is lower than the specified threshold voltage. The output drivers typically source/sink 250mA/500mA; respectively, which is suitable for Plasma Display Panel (PDP) application, motor drive inverter, and switching mode power supply applications.

8-SOP



### Ordering Information

Part Number	Package	Operating Temperature Range	Packing Method
FAN73611M <sup>(1)</sup>	8-Lead, Small-Outline Package (SOP)	-40°C ~ 125°C	Tube
FAN73611MX <sup>(1)</sup>			Tape & Reel

#### Note:

1. These devices passed wave soldering test by JESD22A-111.

## Typical Application Diagrams




Figure 1. Step-Down (Buck) DC-DC Converter Application

## Internal Block Diagram




Figure 2. Functional Block Diagram

## Pin Configuration




Figure 3. Pin Configuration (Top View)

## Pin Definitions

Pin #	Name	Description
1	V <sub>DD</sub>	Supply Voltage
2	IN	Logic Input for High-Side Gate Driver Output
3	NC	No Connection
4	GND	Ground
5	NC	No Connection
6	V <sub>S</sub>	High-Voltage Floating Supply Return
7	HO	High-Side Driver Output
8	V <sub>B</sub>	High-Side Floating Supply

## Absolute Maximum Ratings

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.  $T_A=25^\circ\text{C}$  unless otherwise specified.

Symbol	Characteristics	Min.	Max.	Unit
$V_S$	High-Side Floating Offset Voltage	$V_B-25$	$V_B+0.3$	V
$V_B$	High-Side Floating Supply Voltage	-0.3	625.0	V
$V_{HO}$	High-Side Floating Output Voltage	$V_S-0.3$	$V_B+0.3$	V
$V_{DD}$	Low-Side and Logic Supply Voltage	-0.3	25.0	V
$V_{IN}$	Logic Input Voltage	-0.3	$V_{DD}+0.3$	V
$dV_S/dt$	Allowable Offset Voltage Slew Rate		$\pm 50$	V/ns
$P_D$	Power Dissipation <sup>(2, 3, 4)</sup>		0.625	W
$\theta_{JA}$	Thermal Resistance		200	$^\circ\text{C}/\text{W}$
$T_J$	Junction Temperature	-55	+150	$^\circ\text{C}$
$T_{STG}$	Storage Temperature	-55	+150	$^\circ\text{C}$

### Notes:

2. Mounted on 76.2 x 114.3 x 1.6mm PCB (FR-4 glass epoxy material).
3. Refer to the following standards:  
*JESD51-2: Integrated circuits thermal test method environmental conditions, natural convection, and JESD51-3: Low effective thermal conductivity test board for leaded surface mount packages.*
4. Do not exceed power dissipation ( $P_D$ ) under any circumstances.

## Recommended Operating Conditions

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended operating conditions are specified to ensure optimal performance to the datasheet specifications. Fairchild does not recommend exceeding them or designing to absolute maximum ratings.

Symbol	Parameter	Min.	Max.	Unit
$V_B$	High-Side Floating Supply Voltage	$V_S+10$	$V_S+20$	V
$V_S$	High-Side Floating Supply Offset Voltage	$6-V_{DD}$	600	V
$V_{HO}$	High-Side Output Voltage	$V_S$	$V_B$	V
$V_{IN}$	Logic Input Voltage	GND	$V_{DD}$	V
$V_{DD}$	Supply Voltage	10	20	V
$T_A$	Operating Ambient Temperature	-40	+125	$^\circ\text{C}$

## Electrical Characteristics

$V_{BIAS}(V_{DD}, V_{BS}) = 15.0V$  and  $T_A = 25^\circ C$  unless otherwise specified. The  $V_{IN}$  and  $I_{IN}$  parameters are referenced to GND. The  $V_O$  and  $I_O$  parameters are relative to  $V_S$  and are applicable to the respective output HO.


Symbol	Characteristics	Test Condition	Min.	Typ.	Max.	Unit
<b>Power Supply Section</b>						
$I_{QDD}$	Quiescent $V_{DD}$ Supply Current	$V_{IN}=0V$ or $5V$ , $C_{LOAD}=1000pF$		80	140	$\mu A$
$I_{PDD}$	Operating $V_{DD}$ Supply Current	$C_{LOAD}=1000pF$ , $f_{IN}=20KHz$ , RMS value		80	160	$\mu A$
$V_{DDUV+}$ $V_{BSUV+}$	$V_{DD}$ and $V_{BS}$ Supply Under-Voltage Positive Going Threshold Voltage	$V_{DD}=\text{Sweep}$ , $V_{BS}=\text{Sweep}$	7.8	8.8	9.8	V
$V_{DDUV-}$ $V_{BSUV-}$	$V_{DD}$ and $V_{BS}$ Supply Under-Voltage Negative Going Threshold Voltage	$V_{DD}=\text{Sweep}$ , $V_{BS}=\text{Sweep}$	7.3	8.3	9.3	V
$V_{DDHYS}$ $V_{BSHYS}$	$V_{DD}$ and $V_{BS}$ Supply Under-Voltage Lockout Hysteresis Voltage	$V_{DD}=\text{Sweep}$ , $V_{BS}=\text{Sweep}$		0.5		V
$I_{LK}$	Offset Supply Leakage Current	$V_B=V_S=600V$			10	$\mu A$
$I_{QBS}$	Quiescent $V_{BS}$ Supply Current	$V_{IN}=0V$ or $5V$ , $C_{LOAD}=1000pF$		60	100	$\mu A$
$I_{PBS}$	Operating $V_{BS}$ Supply Current	$C_{LOAD}=1000pF$ , $f_{IN}=20KHz$ , RMS Value		420	600	$\mu A$
<b>Input Logic Section</b>						
$V_{IH}$	Logic "1" Input Voltage		2.5			V
$V_{IL}$	Logic "0" Input Voltage				0.8	V
$I_{IN+}$	Logic Input High Bias Current	$V_{IN}=5V$		50	75	$\mu A$
$I_{IN-}$	Logic Input Low Bias Current	$V_{IN}=0V$			2	$\mu A$
$R_{IN}$	Input Pull-Down Resistance		60	100		$K\Omega$
<b>Gate Driver Output Section</b>						
$V_{OH}$	High Level Output Voltage ( $V_{BIAS} - V_O$ )	No Load			0.1	V
$V_{OL}$	Low Level Output Voltage	No Load			0.1	V
$I_{O+}$	Output High, Short-Circuit Pulsed Current	$V_{HO}=0V$ , $V_{IN}=5V$ , PW $\leq 10\mu s$	200	250		mA
$I_{O-}$	Output Low, Short-Circuit Pulsed Current	$V_{HO}=15V$ , $V_{IN}=0V$ , PW $\leq 10\mu s$	400	500		mA
$V_S$	Allowable Negative $V_S$ Pin Voltage for IN Signal Propagation to HO	$V_{BS}=15V$		-9.8	-7.0	V

## Dynamic Electrical Characteristics


$V_{DD}=V_{BS}=15V$ ,  $C_{LOAD}=1000pF$ , and  $T_A=25^\circ C$ , unless otherwise specified.

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
$t_{on}$	Turn-On Propagation Delay Time	$V_S=0V$	70	120	170	ns
$t_{off}$	Turn-Off Propagation Delay Time	$V_S=0V$	70	120	170	ns
$t_r$	Turn-On Rise Time			70	140	ns
$t_f$	Turn-Off Fall Time			30	60	ns


## Typical Characteristics




**Figure 5. Turn-On Propagation Delay vs. Temperature**




**Figure 6. Turn-Off Propagation Delay vs. Temperature**




**Figure 7. Turn-On Rise Time vs. Temperature**



**Figure 8. Turn-Off Fall Time vs. Temperature**




**Figure 9. Quiescent  $V_{DD}$  Supply Current vs. Temperature**




**Figure 10. Quiescent  $V_{BS}$  Supply Current vs. Temperature**


## Typical Characteristics (Continued)




**Figure 11. Operating  $V_{DD}$  Supply Current vs. Temperature**




**Figure 12. Operating  $V_{BS}$  Supply Current vs. Temperature**




**Figure 13.  $V_{DD}$  UVLO+ vs. Temperature**



**Figure 14.  $V_{DD}$  UVLO- vs. Temperature**



**Figure 15.  $V_{BS}$  UVLO+ vs. Temperature**



**Figure 16.  $V_{BS}$  UVLO- vs. Temperature**

## Typical Characteristics (Continued)




Figure 17. Logic HIGH Input Voltage vs. Temperature




Figure 18. Logic LOW Input Voltage vs. Temperature




Figure 19. Logic HIGH Input Bias Current vs. Temperature




Figure 20. Input Pull-Down Resistance vs. Temperature




Figure 21. High-Level Output Voltage vs. Temperature






Figure 22. Low-Level Output Voltage vs. Temperature


### Typical Characteristics (Continued)




**Figure 23. Allowable Negative  $V_S$  Voltage vs. Temperature**




**Figure 24. Allowable Negative  $V_S$  Voltage vs. Supply Voltage**




**Figure 25. Turn-On Propagation Delay vs. Supply Voltage**



**Figure 26. Turn-Off Propagation Delay vs. Supply Voltage**




**Figure 27. Turn-On Rise Time vs. Supply Voltage**




**Figure 28. Turn-Off Fall Time vs. Supply Voltage**


### Typical Characteristics (Continued)




**Figure 29. Quiescent  $V_{DD}$  Supply Current vs. Supply Voltage**



**Figure 30. Quiescent  $V_{BS}$  Supply Current vs. Supply Voltage**




**Figure 31. Operating  $V_{DD}$  Supply Current vs. Supply Voltage**




**Figure 32. Operating  $V_{BS}$  Supply Current vs. Supply Voltage**

## Switching Time Definitions




FAN73611 Rev.02



FAN73611 Rev.02

Figure 33. Switching Time Test Circuit and Waveform Definitions



FAN73611 Rev.03

Figure 34. Floating Supply Voltage Transient Test

## Physical Dimensions




Figure 35. 8-Lead, Small Outline Package (SOP)

Package drawings are provided as a service to customers considering Fairchild components. Drawings may change in any manner without notice. Please note the revision and/or date on the drawing and contact a Fairchild Semiconductor representative to verify or obtain the most recent revision. Package specifications do not expand the terms of Fairchild's worldwide terms and conditions, specifically the warranty therein, which covers Fairchild products.

Always visit Fairchild Semiconductor's online packaging area for the most recent package drawings:  
<http://www.fairchildsemi.com/packaging/>



#### TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

AccuPower™ F-PFST™  
 Auto-SPM™ FRFET®  
 Build it Now™ Global Power Resource™  
 CorePLUS™ Green FPST™  
 CorePOWER™ Green FPST™ e-Series™  
 CROSSVOLT™ Gmax™  
 CTL™ GTO™  
 Current Transfer Logic™ IntelliMAX™  
 DEUXPEED® ISOPLANAR™  
 Dual Cool™ MegaBuck™  
 EcoSPARK® MICROCOUPLER™  
 EfficientMax™ MicroFET™  
 ESBCTM MicroPak™  
 F® MicroPak2™  
 Fairchild® MillerDrive™  
 Fairchild Semiconductor® MotionMax™  
 FACT Quiet Series™ Motion-SPM™  
 FACT® OptoHIT™  
 FAST® OPTOLOGIC®  
 FastCore™ OPTOPLANAR®  
 FETBench™ PDP SPM™  
 FlashWriter®  
 FPST™

Power-SPM™  
 PowerTrench®  
 PowerXSTM  
 Programmable Active Droop™  
 QFET®  
 QS™  
 Quiet Series™  
 RapidConfigure™  
 Saving our world, 1mW/W/kW at a time™  
 SignalWise™  
 SmartMax™  
 SMART START™  
 SPM®  
 STEALTH™  
 SuperFET™  
 SuperSOT™-3  
 SuperSOT™-6  
 SuperSOT™-8  
 SupreMOS®  
 SyncFET™  
 Sync-Lock™

**SYSTEM GENERAL**  
 The Power Franchise®  
**power franchise**  
 TinyBoost™  
 TinyBuck™  
 TinyCalc™  
 TinyLogic®  
 TINYOPTO™  
 TinyPower™  
 TinyPWM™  
 TinyWire™  
 TrFault Detect™  
 TRUECURRENT™  
 μSerDes™  
**μ**  
 UHC®  
 Ultra FRFET™  
 UniFET™  
 VCXTM  
 VisualMax™  
 XSTM

\* Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

#### DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

#### LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

#### ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, [www.fairchildsemi.com](http://www.fairchildsemi.com), under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

#### PRODUCT STATUS DEFINITIONS

##### Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative / In Design	Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.
No Identification Needed	Full Production	Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.
Obsolete	Not In Production	Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.

Rev. I49