


Restricted to: General Release


USED ON

THIS DRAWING IS A CONTROLLED DOCUMENT  
REV: 20080828



**Left Side**

Connector(s): MT-RJ SECURE (No Pins)  
 Mode: SM  
 Housing Color: Slate  
 Geom. Spec: 115-1215



VIEW C-C  
NOT TO SCALE

**Fiber Path**

Fiber A - - B  
 Fiber B - - A

**Notes:**

- 1 Product and Processing must meet requirements of Tyco Electronics Standard 230-702
- 2 Label 2 will not be present on any cable assembly less than 5 meters long.
- 3 Includes dust caps (not shown on print).
- 4 IL and RL tested at 1310nm.

**Right Side**

Connector(s): SC-Duplex  
 Mode: SM  
 Housing Color: Blue  
 Geom. Spec: N/A

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS. IT IS THE PROPERTY OF TYCO ELECTRONICS AND IS NOT TO BE DISCLOSED TO ANY OTHER PERSON OR ENTITY WITHOUT THE WRITTEN AUTHORIZATION OF TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA.

LOC  
 CE  
 DIST  
 16

B	Rev Per EC#	06-021324	9/13/2006	-	MK		
P	LTR	REVISION RECORD	DATE	DIN	APVD		

DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:
meters	0 PLC ± .
	1 PLC ± .
	2 PLC ± .
	3 PLC ± .
	4 PLC ± .

Customer Print

DIN	Cable Assy Configurator	MATERIAL	HEAT TREAT
CHK	Michael Kepko		
APVD	Michael Kepko	<b>AMP</b> Tyco Electronics, Inc. Harrisburg, PA 17105-3608	
NAME	FO C/A - 2 fiber, SM, OFNR (Riser) jacket, MT-RJ SECURE (No Pins) to SC-Duplex		
SCALE	SIZE	DRAWING NO	SHEET
NTS	A2	C- 6828247	1 of 3
			REV B

8 | 7 | 6 | 5 | 4 | 3 | 2 | 1

Restricted to: General Release

USED ON

THIS DRAWING IS A CONTROLLED DOCUMENT.

Part #	L (meters)	L (feet)	MT-RJ SECURE (No Pins), Slate		SC-Duplex, Blue	
			IL (dB)	RL (dB)	IL (dB)	RL (dB)
0-6828247-1	0.950 - 1.050	3.11 - 3.44	0.5	26	0.5	55
0-6828247-2	1.950 - 2.050	6.39 - 6.72	0.5	26	0.5	55
0-6828247-3	2.950 - 3.050	9.67 - 10.00	0.5	26	0.5	55
0-6828247-4	3.920 - 4.080	12.86 - 13.38	0.5	26	0.5	55
0-6828247-5	4.920 - 5.080	16.14 - 16.66	0.5	26	0.5	55
0-6828247-6	5.920 - 6.080	19.42 - 19.94	0.5	26	0.5	55
0-6828247-7	6.920 - 7.080	22.70 - 23.22	0.5	26	0.5	55
0-6828247-8	7.920 - 8.080	25.98 - 26.50	0.51	26	0.51	55
0-6828247-9	8.850 - 9.150	29.03 - 30.01	0.51	26	0.51	55
1-6828247-0	9.850 - 10.150	32.31 - 33.30	0.51	26	0.51	55
1-6828247-1	10.850 - 11.150	35.59 - 36.58	0.51	26	0.51	55
1-6828247-2	11.850 - 12.150	38.87 - 39.86	0.51	26	0.51	55
1-6828247-3	12.850 - 13.150	42.15 - 43.14	0.51	26	0.51	55
1-6828247-4	13.850 - 14.150	45.43 - 46.42	0.51	26	0.51	55
1-6828247-5	14.850 - 15.150	48.72 - 49.70	0.51	26	0.51	55
1-6828247-6	15.840 - 16.160	51.96 - 53.01	0.51	26	0.51	55
1-6828247-7	16.830 - 17.170	55.21 - 56.33	0.51	26	0.51	55
1-6828247-8	17.820 - 18.180	58.46 - 59.64	0.51	26	0.51	55
1-6828247-9	18.810 - 19.190	61.71 - 62.95	0.51	26	0.51	55
2-6828247-0	19.800 - 20.200	64.96 - 66.27	0.51	26	0.51	55
2-6828247-1	20.790 - 21.210	68.20 - 69.58	0.51	26	0.51	55
2-6828247-2	21.780 - 22.220	71.45 - 72.90	0.52	26	0.52	55
2-6828247-3	22.770 - 23.230	74.70 - 76.21	0.52	26	0.52	55
2-6828247-4	23.760 - 24.240	77.95 - 79.52	0.52	26	0.52	55
2-6828247-5	24.750 - 25.250	81.20 - 82.84	0.52	26	0.52	55
2-6828247-6	25.740 - 26.260	84.44 - 86.15	0.52	26	0.52	55
2-6828247-7	26.730 - 27.270	87.69 - 89.46	0.52	26	0.52	55
2-6828247-8	27.720 - 28.280	90.94 - 92.78	0.52	26	0.52	55
2-6828247-9	28.710 - 29.290	94.19 - 96.09	0.52	26	0.52	55
3-6828247-0	29.700 - 30.300	97.44 - 99.40	0.52	26	0.52	55
3-6828247-1	30.690 - 31.310	100.68 - 102.72	0.52	26	0.52	55
3-6828247-2	31.680 - 32.320	103.93 - 106.03	0.52	26	0.52	55
3-6828247-3	32.670 - 33.330	107.18 - 109.35	0.52	26	0.52	55
3-6828247-4	33.660 - 34.340	110.43 - 112.66	0.52	26	0.52	55
3-6828247-5	34.650 - 35.350	113.68 - 115.97	0.52	26	0.52	55
3-6828247-6	35.640 - 36.360	116.92 - 119.29	0.53	26	0.53	55
3-6828247-7	36.630 - 37.370	120.17 - 122.60	0.53	26	0.53	55
3-6828247-8	37.620 - 38.380	123.42 - 125.91	0.53	26	0.53	55
3-6828247-9	38.610 - 39.390	126.67 - 129.23	0.53	26	0.53	55
4-6828247-0	39.600 - 40.400	129.92 - 132.54	0.53	26	0.53	55
5-6828247-0	49.500 - 50.500	162.40 - 165.68	0.54	26	0.54	55


Qty	U of M	Description	Item No.
1	piece	DUST COVER, MT-RJ	1
1	piece	SPRING, MT-RJ, 3.8 DESIGN	2
1	piece	PIN KEEPER, 3.8MM	3
1	piece	MT-RJ, SPRING PUSH, UNIVERSAL	4
1	piece	CRIMP EYELET, MT-RJ	5
1	piece	MT-RJ Keyed Connector Housing - Slate	6
2	piece	LC, SC, FC Straight Boot, Blue	7
1	piece	MT-RJ FERRULE, THERMOPLAST SM	8
2	piece	SC Simplex Housing, Blue	9
2	piece	2.5mm ferrule cover	10
AR	meter	2 fiber, SM, 1.8 mm, Twinzip, Yellow, OFNR (Riser)	11
1	piece	MT-RJ TwinZip Bend Limiting Boot, Blue	12
2	piece	SC Duplex Clip	13
2	piece	Eyelet/Shrink tube assembly - Yellow	14
2	piece	CONN ASSY, SM, SC 1.6MM/125.5UM	15
2	piece	Trace Label	16


THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION. IT IS THE PROPERTY OF TYCO ELECTRONICS CORPORATION AND IS NOT TO BE DISCLOSED TO ANY OTHER PERSON OR ENTITY WITHOUT THE WRITTEN AUTHORIZATION OF TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA.

LOC  
 CE  
 DIST  
 16

B	Rev Per	EC#	06-021324	9/13/2006	-	MK
P	LTR	REVISION RECORD		DATE	DN	APVD

DIMENSIONS: meters  
 TOLERANCES UNLESS OTHERWISE SPECIFIED:  
 0 PLC ±  
 1 PLC ±  
 2 PLC ±  
 3 PLC ±  
 4 PLC ±



DIN	Cable Assy Configurator	MATERIAL		HEAT TREAT	
CHK	Michael Kepko				
APVD	Michael Kepko				
NAME	FO C/A - 2 fiber, SM, OFNR (Riser) jacket, MT-RJ SECURE (No Pins) to SC-Duplex				
SCALE	NTS	SIZE	A2	DRAWING NO	C- 6828247
SHEET	2 of 3	REV	B		

THIS DRAWING IS A CONTROLLED DOCUMENT. BFC#D

**Label 1** Per specification 107-1645-1

Trace # - Bar Code  
 Trace # - Human Readable  
 Part Number  
 Country of Origin

**This label is used on all lengths on this drawing.**

**Label 2** Per specification 107-1645-1

Trace # - Bar Code  
 Trace # - Human Readable  
 Part Number  
 Country of Origin

**This label is used on all lengths on this drawing.**

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION. IT IS NOT TO BE DISCLOSED TO ANY OTHERS WITHOUT THE WRITTEN AUTHORIZATION OF TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA

LOC  
CE  
DIST  
16

B	Rev Per EC#	06-021324	9/13/2006	-	MK	
P	LTR	REVISION RECORD	DATE	DIN	APVD	

DIMENSIONS: meters	TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± .	1 PLC ± .
2 PLC ± .	3 PLC ± .
4 PLC ± .	

Customer Print

DIN	Cable Assy Configurator	MATERIAL	HEAT TREAT
OK	Michael Kepko		
APVD	Michael Kepko	<b>AMP</b> Tyco Electronics, Inc. Harrisburg, PA 17105-3608	
NAME	FO C/A - 2 fiber, SM, OFNR (Riser) jacket, MT-RJ SECURE (No Pins) to SC-Duplex		
SCALE	SIZE	DRAWING NO	SHEET
NTS	A2	<b>C- 6828247</b>	3 of 3
			REV <b>B</b>

A B C D