Data sheet

6ES7193-6BP40-0DA1



SIMATIC ET 200SP, BaseUnit BU15-P16+A0+12D/T, BU type A1, Push-in terminals, with $2x\ 5$ add-on terminals, New load group, WxH: 15 mm x 141 mm, with temperature acquisition

General information	
Product type designation	BU type A1
HW functional status	FS10 and higher
Supply voltage	
Rated value (DC)	24 V
external protection for power supply lines	Yes; 24 V DC/10 A miniature circuit breaker with type B or C tripping characteristic
Current carrying capacity	
For P1 and P2 bus, max.	10 A
For process terminals, max.	2 A
Hardware configuration	
Additional terminals	Yes
Temperature sensor	Yes
Formation of potential groups	
 New potential group 	Yes
Potential group continued from the left	No
Slots	
Number of slots	1; Type A1
Potential separation	
between the potential groups	Yes
Isolation	
Isolation tested with	707 V DC (type test)
Ambient conditions	
Ambient temperature during operation	
 horizontal installation, min. 	-30 °C
 horizontal installation, max. 	60 °C
 vertical installation, min. 	-30 °C
vertical installation, max.	50 °C
Altitude during operation relating to sea level	
Installation altitude above sea level, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
Accessories	
Color coding labels	
 for process terminals 	CC00 to CC09
 for AUX terminals 	does not exist
for add-on terminals	CC74
connection method / header	
Terminals	
 Terminal type 	Push-in terminal
 Conductor cross-section, min. 	0.14 mm²; AWG 26

 Conductor cross-section, max. Number of process terminals to I/O module Number of terminals to AUX bus Number of add-on terminals 	2.5 mm²; AWG 14 16 0 2x5
 Number of add-off terminals Number of terminals with connection to P1 and P2 bus 	2
Dimensions	
Width	15 mm
Height	141 mm
Depth	35 mm
Weights	
Weight, approx.	50 g

last modified: 1/16/2021 🖸