

AC Power Supply - 12VDC.
Universal plugs (US, EU, UK, AU) to
2.1mm locking barrel plug.
Compatibility: Digi TransPort
WR41 (locking power cord
models), Digi TransPort WR44
(locking power cord models), Digi
TransPort WR21.

PART NUMBERS



North America: **76000823**

International: **76000823**

[See larger view](#)

Input Specifications:

- Rated input voltage rating: 100VAC to 240VAC
- Input frequency: 47 Hz to 63 Hz
- Rated input current: < 0.6 A RMS MAX
- Max. in-rush current: 30A max. @ cold start 120VAC, 60A max. @ cold start 230VAC
- Input Plug Type: Includes four input connectors: NA, EU, UK, and AU. Leakage current: < 0.3 mA @ 240 VAC

Output Specifications:

- Output Voltage: 12VDC
- Load current: 1.5A
- Output Plug: 9.5 x 5.5 x 2.1mm locking barrel plug
- Max. output power: 18W max.

Environment:

- Operating Temperature: 0°C TO 40° C
- Storage Temperature: -40°C TO 80° C

Dimensions:

- Size: 84 x 56 x 37.9mm
- Cord Length: 6ft

Approvals:

- Certifications: UL, cUL, CE, RoHS

Contact a Digi expert and get started today!

[CONTACT US](#)