

## **Specification Sheet**

Part Number: 170-03142

Split wrap design installs quickly, saving assembly time and future accessibility without disassembly.

Unique construction retains shape and rigidity throughout operating temperature range.



Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.

Self wrapping design eliminates the need for fasteners.

Provides a greater flexibility than spiralwrap or convoluted tubing.

Braided Sleeving, Split Wrap, Flame Retardant, 0.5" Dia, PET, Black, 150 ft/bulk reel

Article Number 170-03142

Type BSSWFR120B

Color Black (BK)

Quantity Per reel

**Product Description** 

Used when flame retardancy is a primary requirement, this protection option incorporates a lateral split which allows the tube to open up to accommodate a variety of bundling requirements. The semi-rigid braid configuration simply closes around the entire installation without the need for any additional fasteners. Split wrap flame retardant braided sleeving is self-extinguishing and complies with UL VW-1 standards where cables exit a wall and need to be managed for an uncluttered, clean appearance.

Short Description	Braided Sleeving, Split Wrap, Flame Retardant, 0.5" Dia, PET, Black 150 ft/bulk reel			
Global Part Name	BSSWFR120B-PET-BK			
Length L (Imperial)	150.0			
Length L (Metric)	45.7			
Bundle Diameter Min (Imperial)	0.5			
Bundle Diameter Min (Metric)	12.7			
Bundle Diameter Max (Imperial)	0.50			
Bundle Diameter Max (Metric)	12.7			
Diameter D (Imperial)	0.50			
Diameter D (Metric)	12.7			
Nominal Diameter (Imperial)	0.5			
Nominal Diameter (Metric)	12.7			
Wall Thickness WT (Imperial)	0.025			
Wall Thickness WT (Metric)	0.64			

Material	Polyester (PET)

Material Shortcut PET

Flammability FAR 25 UL 224 VW-1

Halogen Free Yes

UV Resistant (Yes/No) No

Operating Temperature -94°F to +257°F (-70°C to +125°C)

Reach Compliant (Article 33)

Yes

ROHS Compliant Yes

Certification/Specification ASTM E 662 ASTM E 162 ASTM 1354

UL Recognized (US)
Yes

Package Quantity (Imperial) 150.0

Package Quantity (Metric) 45.7

Customs Number 5808100000

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global

customers. HellermannTyton operates (www.hellermann.tyton.com).	in 39 countries	s, with North American headq	uarters in Milw	aukee, Wisconsin.
© 2023 HellermannTyton. All Rights	Reserved. Contact Us	RoHS/WEEE Compliance	Disclaimer	Terms and Conditions
		·		