

## Adapter - HC-D-TA-PG16-PLR-BK - 1411353

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



EVO plastic adapter with bayonet locking, for EVO housing series D, for Pg16 screw connections.



### Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	20.0 g
Custom tariff number	39269097
Country of origin	Poland

### Technical data

#### Ambient conditions

Degree of protection	IP66 (DIN IEC 60529)
Ambient temperature (operation)	-40 °C ... 125 °C

#### General

Type of the screw connection	Pg16
Material	PA
Housing material	PA
Seal material	NBR
Thread type on connection side	Bayonet D plastic
Thread type on seal side	Pg16
Flammability rating according to UL 94	V2

#### Standards and Regulations

Flammability rating according to UL 94	V2
--	----

# Adapter - HC-D-TA-PG16-PLR-BK - 1411353

## Classifications

eCl@ss

eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 8.0	27440202
eCl@ss 9.0	27440202

ETIM

ETIM 4.0	EC000516
ETIM 5.0	EC000516

## Approvals

Approvals

---

Approvals

EAC

---

Ex Approvals

---

Approvals submitted


---

Approval details

EAC
-----

## Drawings

Dimensional drawing



Dimensional drawing

