SB10-03A2, SB10-03A3

Schottky Rectifier, 30V, 1A



Applications

• High frequency rectification (switching regulators, converters, choppers)

Features

- Low forward voltage (V_F max=0.55V)
- Fast reverse recovery time (t_{rr} max=30ns)
- Low switching noise
- Average rectified current($I_0=1.0A$)

Specifications

Absolute Maximum Ratings at Ta=25°C

Parameter	Symbol	Conditions	Ratings	Unit
Repetitive Peak Reverse Voltage	VRRM		30	V
Nonrepetitive Peak Reverse Surge Voltage	VRSM		35	V
Average Rectified Current	IO	SB10-03A2 50Hz,resistive load,sine wave, Ta=50°C	1.0	A
		(L=8mm,10×10mm ² print land)	1.0	
		SB10-03A3 50Hz,resistive load,sine wave, Ta=46°C	1.0	A
		(L=3mm,5×5mm² print land)	1.0	
Surge Forward Current	IFSM	50Hz sine wave, 1 cycle	40	А
Junction Temperature	Tj		125	°C
Storage Temperature	Tstg		-40 to +125	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.


Electrical Characteristics at Ta=25°C

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Forward Voltage	VF	IF=1.0A			0.55	V
Reverse Current	IR	V _R =30V			1.0	mA
Reverse Recovery Time	t _{rr}	IF=1A, -di/dt=50A/μs			30	ns
Thermal Resistance(Junction-Ambient)	Rth(j-a)	No fin,device only			140	°C/W

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.


Package Dimensions

unit : mm (typ) SB10-03A2



Package Dimensions

unit : mm (typ) SB10-03A3



Resisitive load VR=30V

L = 8 mm

mm

≪—10mm⊏

Printed circuit board

120 140 160

80

100

100°C

80°C

60°C

180°

15

7

10

2 3

20

20

240°

25

300°

Sine wave


f = 100 kHz

30

25

30

15



ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC) or its subsidiaries in the United States and/or other countries. SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf . SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products harms harmeless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable cop