

## WADI heat cable gland


K155-1xxx-zz

Dome nut	Brass CuZn39Pb3, nickel-plated
Sealing insert	Fluorine rubber FKM
Gland body	Brass CuZn39Pb3, nickel-plated
O-ring	Fluorine rubber FKM
Connecting thread	metric, as per EN 60423




### Properties


	<ul style="list-style-type: none"> <li>• especially suitable for high temperature applications</li> <li>• Sealing insert and O-ring have a very good resistance to many chemicals</li> <li>• high UV, ozone and weather resistance</li> <li>• large-area sealing protects the cable</li> <li>• increased anchorage with high retention</li> <li>• wide sealing and clamping range</li> <li>• the inner sealing ring can be removed easily for larger cables</li> </ul>
Temperature range	-40 °C / +200 °C (dynamic)
Protection grade	IP66 / IP67 / IP69
Test standard	EN 62444



### Features

Connecting thread standard length

A	ØC	Ø C1	Ø C2	L	SW1	SW2	H		Part No.
M12x1, 5	3 - 8	3 - 5	5 - 8	6,5	16	16	25,5	100	K155-1012-00
M16x1, 5	5 - 10,5	5 - 7,5	7,5 - 10,5	7,0	20	20	31,5	100	K155-1016-00
M20x1, 5	8 - 15	8 - 10,5	10,5 - 12	8,0	25	25	33	50	K155-1020-00
M25x1, 5	14 - 20,5	14 - 15,5	15,5 - 20,5	8,0	32	32	35,5	50	K155-1025-00

A	ØC	Ø C1	Ø C2	L	SW1	SW2	H	 VPE	Part No.
M32x1, 5	18 - 25,5	18 - 20,5	20,5 - 25,5	9,0	36	36	40,5	25	K155-1032-00
M40x1, 5	24 - 33	24 - 29	29 - 33	9,0	45	45	43	10	K155-1040-00
M50x1, 5	32 - 42	32 - 37,5	37,5 - 42	10,0	55	55	47,5	5	K155-1050-00
M63x1, 5	40 - 53	40 - 46	46 - 53	10,0	70	70	53	5	K155-1063-00