



# CII FC-335 Series Relays

Compact, Hermetically Sealed, Non-Latching Relays

# CII FC-335 Series Relays

Compact, Hermetically Sealed, Non-Latching Relays



## OUTSTANDING PERFORMANCE

- Higher capacity rating over standard M83536 relays
- Mechanical Life Expectancy: >50,000 cycles
- Excellent in switching harsh inductive loads (motor/lamp)
- -70°C to +125°C Temperature range
- 80,000 ft Altitude Rating

## RUGGED

- Hermetically Sealed/ non-latching
- All welded construction
- Corrosion protected metal can

## VERSATILE

- 28 VDC and 115 VAC coils configurations
- Solder hooks and terminal block configurations

## COMPACT/LIGHTWEIGHT

- 1.5 inch cube
- .5 lbs max (227 Grams max)

## MARKETS

- Commercial Aircraft
- Military Aircraft
- Missiles
- Defense Systems

FC-335 Series relays from TE Connectivity (TE) are hermetically sealed devices designed for harsh inductive, motor, and lamp load applications in the aerospace, defense, and marine markets.

Configured as a 3PST/NO (DM), the double make contact design of the CII FC-335 Series relays offer higher capacity rating over most standard M83536 relays. It shares the load across two contact sets, helping to minimize less wear. This helps provide stable performance and helps to extend the relay's life. The relay's all welded design creates a reliable alternative to similar solder sealed relays in the market.

## ADVANTAGES

- Double make contacts and laser welded enclosure design helps to provide stable performance over life of relay
- 35 Amp / 28 Vdc resistive rating. Similar products on the market are rated at 25 Amps.
- Main contacts are suitable for use in 360-800 Hz variable frequency applications
- Higher current capacity ratings over most standard M83536 relays. Excellent for switching harsh inductive, motor and lamp loads

## APPLICATIONS

- Launch Systems
- Power Distribution
- Fuel Pumps
- Guidance and Navigation Systems
- Aircraft Galley/Cabin Equipment
- Weapon Systems
- Ground Support Equipment

## TE Components . . . TE Technology . . . TE Know-how . . .

AMP | AGASTAT | CII | HARTMAN | KILOVAC | MICRODOT | NANONICS | POLAMCO | Raychem  
SEACON | Rochester | DEUTSCH

Empower Engineers to Solve Problems, Moving the World Forward.



**CONFIGURATION**

The FC-335 Series is available in 2 basic configurations:

**Screw Terminals**



**Solder Hooks**



**ORDERING INFORMATION**

Part Number	Terminal	Mounting	Coil
FC-335-CW3	Solder Hook	Stud	28 Vdc
FC-335-CW4	Solder Hook	Stud	28 Vdc (Suppressed)
FC-335-CW8	Solder Hook	Stud	115 Vac, 400 Hz
FC-335-CW9	Solder Hook	Stud	115 Vac, 50/60 Hz
FC-335-SY3	Screw	Bracket	28 Vdc
FC-335-SY4	Screw	Bracket	28 Vdc (Suppressed)
FC-335-SY8	Screw	Bracket	115 Vac, 400 Hz
FC-335-SY9	Screw	Bracket	115 Vac, 50/60 Hz

\* Custom Orders available upon request. Please contact TE.

## LET'S CONNECT

We make it easy to connect with our experts and are ready to provide all the support you need. Just call your local support number or visit [te.com](http://te.com) to chat with a Product Information Specialist.

## Technical Support

[te.com/support-center](http://te.com/support-center)

North America	+1 800 522 6752	Asia Pacific	+86 400 820 6015
North America (Toll)	+1 717 986 7777	Japan	+81 044 844 8180
EMEA/South Africa	+800 0440 5100	Australia	+61 2 9554 2695
EMEA (Toll)	+31 73 624 6999	New Zealand	+64 (0) 9 634 4580
India (Toll-Free)	+800 440 5100		

[te.com/fc-335](http://te.com/fc-335)

AMP, AGASTAT, CII, DEUTSCH, HARTMAN, KILOVAC, MICRODOT, NANONICS, POLAMCO, Raychem, SEACON, TE, TE Connectivity and the TE connectivity (logo) are trademarks of TE Connectivity. Other products, logos, and company names mentioned herein may be trademarks of their respective owners.

While TE Connectivity (TE) has made every reasonable effort to ensure the accuracy of the information herein, nothing herein constitutes any guarantee that such information is error-free, or any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. The TE entity issuing this publication reserves the right to make any adjustments to the information contained herein at any time without notice. All implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose are expressly disclaimed. The dimensions herein are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice.

Consult TE for the latest dimensions and design specifications.

© 2018 TE Connectivity All Rights Reserved.

1-1773949-9 03/18