

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: KFZEDGM-X-5. 08-ZP-IG, equal to Phoenix 1912184 or 2ESDVM-02P TERM BLOCK PLUG 2POS STR 5.08MM to KFZEDGM-X-5. 08-ZP-IG, equal to Phoenix 1912184 or 2ESDVM-02P TERM BLOCK PLUG 2POS STR 5.08MM, GT Cable #150: 18 / 2 Conductors, 2.7X5.4mm OD, SPT-1, 105 Deg.C, 300V, SOLID/RIBBED, Approvals: , 300mm, GlobTek Black	
	Model No. Low voltage cable	
	Part No./Ordering No. PHX19121840M3PHX1912184	Rev A

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

In Addition to GlobTek Inc.'s renewed ISO9001:2008 - Quality Management System Certification, GlobTek Inc. is now certified to:

- ISO13485:2003 - Medical Devices Quality Management System Certification
- ISO14001:2004 - Environmental Management System Certification

ISO Certificates are available online at <https://www.globtek.com/iso-certificates/>

Prop 65 Statement: <https://en.globtek.com/prop-65-statement.pdf>

The acceptance of this specification and use of the product described in this document indicates the acceptance and binding of the customer to Globtek TERMS AND CONDITIONS (attached to the end of this document), which supersede all other agreements, terms, and conditions (<https://en.globtek.com/terms-and-conditions/>).

The purchaser of this product (Customer) agrees that it is their sole responsibility to determine suitability/fitness of the product described in this specification for their application and to take precautions for protection against any hazards attendant to the handling and use of the product.

**Footnote:**

GlobTek Inc. will not be liable for the safety and performance of these power supplies if unauthorized access and repair occurs. End user should consult applicable UL, CSA or EN standards for proper installation instruction.

**Limitation of Use:**

GlobTek products are intended for use with commercial, medical, and/or industrial equipment only. GlobTek product are not authorized for use as mission critical components in life support hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of GlobTek Inc.  
 Contents of this document are subject to change without prior notice.

**Customer Approval of Specification:**

Please approve, sign and send back to GlobTek so we can complete order processing.  
 A delay in receipt of this form will delay delivery schedule.

Company Name: _____	Customer P/N: _____
Quote Number: _____	Date: _____
Authorized Representative Name: _____	Authorized Representative Signature: _____

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: KFZEDGM-X-5. 08-ZP-IG, equal to Phoenix 1912184 or 2ESDVM-02P TERM BLOCK PLUG 2POS STR 5.08MM to KFZEDGM-X-5. 08-ZP-IG, equal to Phoenix 1912184 or 2ESDVM-02P TERM BLOCK PLUG 2POS STR 5.08MM, GT Cable #150: 18 / 2 Conductors, 2.7X5.4mm OD, SPT-1, 105 Deg.C, 300V, SOLID/RIBBED, Approvals: , 300mm, GlobTek Black	
	Model No. Low voltage cable	
Part No./Ordering No. PHX19121840M3PHX1912184		Rev A

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

## REVISION HISTORY

REV	DESCRIPTION	SUB	DATE	APPROVED
A	Initial release	DR	01/13/2020	QA

Cordset Information:

CordsetColor:GlobTek Black

Cord Length (mm):300

NOTES:

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: KFZEDGM-X-5. 08-ZP-IG, equal to Phoenix 1912184 or 2ESDVM-02P TERM BLOCK PLUG 2POS STR 5.08MM to KFZEDGM-X-5. 08-ZP-IG, equal to Phoenix 1912184 or 2ESDVM-02P TERM BLOCK PLUG 2POS STR 5.08MM, GT Cable #150: 18 / 2 Conductors, 2.7X5.4mm OD, SPT-1, 105 Deg.C, 300V, SOLID/RIBBED, Approvals: , 300mm, GlobTek Black	
	Model No. Low voltage cable	
	Part No./Ordering No. PHX19121840M3PHX1912184	Rev A

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

END A



Mates with 1924525, 1924088

END B




Mates with 1924525, 1924088

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: KFZEDGM-X-5. 08-ZP-IG, equal to Phoenix 1912184 or 2ESDVM-02P TERM BLOCK PLUG 2POS STR 5.08MM to KFZEDGM-X-5. 08-ZP-IG, equal to Phoenix 1912184 or 2ESDVM-02P TERM BLOCK PLUG 2POS STR 5.08MM, GT Cable #150: 18 / 2 Conductors, 2.7X5.4mm OD, SPT-1, 105 Deg.C, 300V, SOLID/RIBBED, Approvals: , 300mm, GlobTek Black
	Model No. Low voltage cable
Part No./Ordering No. PHX19121840M3PHX1912184	Rev A

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

CABLE IMAGE



GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: KFZEDGM-X-5. 08-ZP-IG, equal to Phoenix 1912184 or 2ESDVM-02P TERM BLOCK PLUG 2POS STR 5.08MM to KFZEDGM-X-5. 08-ZP-IG, equal to Phoenix 1912184 or 2ESDVM-02P TERM BLOCK PLUG 2POS STR 5.08MM, GT Cable #150: 18 / 2 Conductors, 2.7X5.4mm OD, SPT-1, 105 Deg.C, 300V, SOLID/RIBBED, Approvals: , 300mm, GlobTek Black	
	Model No. Low voltage cable	
Part No./Ordering No. PHX19121840M3PHX1912184		Rev A

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

End A Code:PHX1912184 Description:KFZEDGM-X-5. 08-ZP-IG, equal to Phoenix 1912184 or 2ESDVM-02P TERM BLOCK PLUG 2POS STR 5.08MM Rating (V):300 Rating (A):16.0 Gender:Female Overmolded:No	Cable Code:150 Description:GT Cable #150: 18 / 2 Conductors, 2.7X5.4mm OD, SPT-1, 105 Deg.C, 300V, SOLID/RIBBED, Approvals: Color:GlobTek Black Wire Gauge(AWG):18 Cond:2 Type:SPT-1 Temperature:105° C Amps:10 Volts:300 OD:2.7X5.4 ConductorsColors:SOLID/RIBBED	End B Code:PHX1912184 Description:KFZEDGM-X-5. 08-ZP-IG, equal to Phoenix 1912184 or 2ESDVM-02P TERM BLOCK PLUG 2POS STR 5.08MM Rating (V):300 Rating (A):16.0 Gender:Female Overmolded:No
--	---	--

Overall cable rating:UL 300V/IEC600V/16A

Plug Approvals	Cable Approvals	Connector Approvals
----------------	-----------------	---------------------



UL RECOGNIZED

AGENCY ONLINE DOCUMENTS	<a href="http://en.globtek.com/cordsets/">http://en.globtek.com/cordsets/</a>
RoHS/RoHS3 Declaration	<a href="https://www.globtek.com/pdf/rohs_cert/01t3a000004eZDIAA2">https://www.globtek.com/pdf/rohs_cert/01t3a000004eZDIAA2</a>
REACH Declaration	<a href="https://www.globtek.com/pdf/iso_certificates/REACH.pdf">https://www.globtek.com/pdf/iso_certificates/REACH.pdf</a>
Conflict Minerals Declaration	<a href="https://www.globtek.com/pdf/conflict-minerals.pdf">https://www.globtek.com/pdf/conflict-minerals.pdf</a>
Prop 65 Statement	<a href="https://en.globtek.com/prop-65-statement.pdf">https://en.globtek.com/prop-65-statement.pdf</a>
CE.UKCA.Cord	<a href="https://globtek.secure.force.com/spec/ec_decl_product_model_family_incl_cord?id=01t3a000004eZDI">https://globtek.secure.force.com/spec/ec_decl_product_model_family_incl_cord?id=01t3a000004eZDI</a>

IPXY rating is based on 3rd party testing and customers should check suitability and test system level IPXY rating before ordering.

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: KFZEDGM-X-5. 08-ZP-IG, equal to Phoenix 1912184 or 2ESDVM-02P TERM BLOCK PLUG 2POS STR 5.08MM to KFZEDGM-X-5. 08-ZP-IG, equal to Phoenix 1912184 or 2ESDVM-02P TERM BLOCK PLUG 2POS STR 5.08MM, GT Cable #150: 18 / 2 Conductors, 2.7X5.4mm OD, SPT-1, 105 Deg.C, 300V, SOLID/RIBBED, Approvals: , 300mm, GlobTek Black	
	Model No. Low voltage cable	
	Part No./Ordering No. PHX19121840M3PHX1912184	Rev A

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

Hanking:  
 Description:  
 Image:

Notes/Modifications/Customizations (notes in this section supersede the values shown in the standard spec):  
 Mates with 1924525, 1924088