


## SPECIFICATIONS

## SDDC20G2W

### OUTLINES DIMENSIONS



**Notes:**

1. All Dimensions are in millimeters (inches).
2. Tolerance is  $\pm 0.25\text{mm}$  (0.01") unless otherwise noted.
3. Specifications are subject to change without notice.






| Part Number | Chip Material | Color of Emission | Lens Type     | Description    |
|-------------|---------------|-------------------|---------------|----------------|
| SDDC20G2W   | InGaAlP       | Green             | White Segment | Common Cathode |



ChromeLED Corp. reserves the right to make changes at any time in order to supply the best product possible. The most current version of this document will always be available at: [www.chromeled.com](http://www.chromeled.com)

## TYPICAL INTERNAL EQUIVALENT CIRCUIT

Recommended Soldering Pattern



(Common Cathode)



ChromeLED Corp. reserves the right to make changes at any time in order to supply the best product possible. The most current version of this document will always be available at: [www.chromeled.com](http://www.chromeled.com)

**ABSOLUTE MAXIMUM RATINGS (TA=25°C)**

| Parameter  | Symbol | Max Rating | Unit |
|--|--------|------------|------|
| Power Dissipation  | PD     | 70         | mW   |
| Pulse Forward Current  | IFP    | 90         | mA   |
| Continuous Forward Current   | IF     | 25         | mA   |
| Reverse Voltage Segment  | VR     | 5          | V    |
| Operating Temperature Range  | TOPR   | -40~+105   | °C   |
| Storage Temperature Range  | TSTG   | -40~+105   | °C   |
| IFP = Pulse Width ≤ 10 ms, Duty Ratio ≤1/10. Soldering Condition: 260 °C/ 5sec |        |            |      |

**OPTICAL-ELECTRICAL CHARACTERISTICS (TA=25°C)**

| Parameter               | Symbol | Test Condition | Value |     |     | Unit |
|-------------------------|--------|----------------|-------|-----|-----|------|
|                         |        |                | Min   | Typ | Max |      |
| Luminous Intensity      | IV     | IF = 20mA      | -     | 6   | -   | mcd  |
| Forward Voltage         | VF     | IF = 20mA      | -     | 2.1 | 2.6 | V    |
| Reverse Leakage Current | IR     | VR = 5V        | -     | -   | 10  | µA   |
| Dominant Wavelength     | λd     | IF = 20mA      | -     | 570 | -   | nm   |
| Peak Wavelength         | Δp     | IF = 20mA      | -     | 573 | -   | nm   |



ChromeLED Corp. reserves the right to make changes at any time in order to supply the best product possible. The most current version of this document will always be available at: [www.chromeled.com](http://www.chromeled.com)

## OPTICAL CHARACTERISTIC CURVES

(25 °C Free Air Temperature Unless Otherwise Specified)




Fig.1 FORWARD CURRENT VS. FORWARD VOLTAGE




Fig.2 RELATIVE INTENSITY VS. FORWARD CURRENT




Fig.3 FORWARD VOLTAGE VS. TEMPERATURE




Fig.4 RELATIVE INTENSITY VS. TEMPERATURE




Fig.5 RELATIVE INTENSITY VS. WAVELENGTH




Fig.6 MAX. ALLOWABLE DC CURRENT VS. AMBIENT TEMPERATURE




ChromeLED Corp. reserves the right to make changes at any time in order to supply the best product possible. The most current version of this document will always be available at: [www.chromeled.com](http://www.chromeled.com)

**SOLDERING CONDITIONS – DISPLAY TYPE LED**
**● RECOMMEND SOLDERING PROFILE**

SMT Soldering Profile

Pb free reflow soldering Profile


**● SOLDERING IRON**

Basic specification :  $\leq 4$  seconds when 260°C, If temperature is higher, time should be shorter (+10°C→1 sec). Power dissipation of iron should be smaller than 15W, and temperature should be controllable. Surface temperature of the device should be under 230°C.

**● REWORK**

Customer must finish rework within  $\leq 3$  sec under 350°C.



ChromeLED Corp. reserves the right to make changes at any time in order to supply the best product possible. The most current version of this document will always be available at: [www.chromeled.com](http://www.chromeled.com)