



Main

Range of Product	Telemecanique Photoelectric sensors XU
Accessory / separate part designation	Focusers for diffuse system fiber optics
Accessory / Separate Part Type	Focusers
Accessory / separate part category	Sensor accessories
Accessory / separate part destination	XUY glass fiber optic
Product Specific Application	For pinpoint reading of reference marks, contrasts, faults

Complementary

Product Compatibility	XUYFVPSD XUYFVPML XUYFVPTD XUYFVPSL XUYFVPTL XUYFVPMD
[Sn] nominal sensing distance	32.81 ft (10 m)
Net Weight	0.01 lb(US) (0.003 kg)

Ordering and shipping details

Category	22481-SENSORS, PHOTOELECTRIC
Discount Schedule	DS2
GTIN	3389119009300
Nbr. of units in pkg.	1
Package weight(Lbs)	0.07 oz (2.0 g)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.94 in (10 cm)
Package 1 width	2.36 in (6 cm)
Package 1 Length	1.18 in (3 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

Contractual warranty

Warranty

18 months
