



ELECTRONICS, INC.
44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089
<http://www.nteinc.com>

NTE56015 thru NTE56018 TRIAC, 25 Amp

Description:

The NTE56015 through NTE56018 series of TRIACs are high performance glass passivated PNPN devices in a TO220 type package designed for general purpose applications where moderate gate sensitivity is required.

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Repetitive Peak Off-State Voltage ($T_J = -40^\circ$ to $+125^\circ\text{C}$, $R_{GK} = 1\text{k}\Omega$), V_{DRM}

NTE56015	200V
NTE56016	400V
NTE56017	600V
NTE56018	800V

On-State Current (All Conduction Angles, $T_C = +85^\circ\text{C}$), $I_T(\text{RMS})$ 25A

Non-Repetitive On-State Current (Half Cycle), I_{TSM}

60Hz	260A
50Hz	250A

Fusing Current ($t = 10\text{ms}$), I^2t 312A²s

Peak Gate Current ($t = 10\mu\text{s}$ Max), I_{GM} 4A

Peak Gate Dissipation ($t = 10\mu\text{s}$ Max), P_{GM} 10W

Gate Dissipation ($t = 20\text{ms}$ Max), $P_{G(AV)}$ 1W

Operating Junction Temperature Range, T_J -40° to $+125^\circ\text{C}$

Storage Temperature Range, T_{stg} -40° to $+125^\circ\text{C}$

Thermal Resistance, Junction-to-Case, R_{thJC} 1.5K/W

Thermal Resistance, Junction-to-Ambient, R_{thJA} 60K/W

Lead Temperature (During Soldering, 1.6mm from case, 10sec max), T_L $+250^\circ\text{C}$

Electrical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Off-State Leakage Current	I_{DRM}	$V_D = V_{DRM}$, $R_{GK} = 1\text{k}\Omega$, $T_J = +25^\circ\text{C}$	-	-	10	μA
		$V_D = V_{DRM}$, $R_{GK} = 1\text{k}\Omega$, $T_J = +125^\circ\text{C}$	-	-	3	mA
On-State Voltage	V_T	$I_T = 37.5\text{A}$, $T_J = +25^\circ\text{C}$	-	-	1.4	V
On-State Threshold Voltage	$V_{T(TO)}$	$T_J = +125^\circ\text{C}$	-	-	0.85	V
On-State Slope Resistance	r_T	$T_J = +125^\circ\text{C}$	-	-	13	$\text{m}\Omega$

Electrical Characteristics (Cont'd): ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Gate Trigger Current	I_{GT}	$V_D = 12\text{V}$, Note 1	-	-	50	mA
Gate Trigger Voltage	V_{GT}	$V_D = 12\text{V}$, All Quadrants	-	-	2.5	V
Holding Current	I_H	$R_{GK} = 1\text{k}\Omega$	-	-	50	mA
Critical Rate-of-Rise	dv/dt	$V_D = 0.67 \times V_{DRM}$, $R_{GK} = 1\text{k}\Omega$, $T_J = +125^\circ\text{C}$	500	-	-	V/ μ s
Critical Rate-of-Rise, Off-State	dv/dt_C	$I_T = 25\text{A}$, $di/dt = 11\text{A/ms}$, $T_C = +85^\circ\text{C}$	5	-	-	V/ μ s

Note 1. For either polarity of gate voltage with reference to electrode MT₁.

