72 INCHES LENGTH





Connector A 132117RP SMA Jack Straight Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B 122454 TNC Jack Right Angle Bulkhead - Rear Mount Brass Nickel + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

Connector A			Cable		Connector B	
Part #:	132117RP	Part #:	RG-174	Part #:	122454	
Description:	SMA JACK RP RG316 500	Description:	RG-174 - PE 0.1	Description:	TNC R/A BHD JK RG174 RG316 LMR100	
Type:	SMA	Dielectric:	PE	· ·	500	
Gender:	Jack	Shielding:	Braid	Type:	TNC	
Body Type:	Straight	Diameter:	0.1	Gender:	Jack	
Contact Type:	Crimp	Impedance:	50 Ohm	Body Type:	Right Angle	
Polarity:	Reverse	Sheathing:	None	Contact Type:	Solder	
Impedance:	50 Ohm	Testing:	Continuity Hi-Pot	Polarity:	Standard	
Mounting:	Cable	Length:	72 Inches	Impedance:	50 Ohm	
Body Material:	Brass			Mounting:	Bulkhead - Rear Mount	
Body Finish:	Gold			Body Material:	Brass	
IP Rating:	None			Body Finish:	Nickel	
Contact Material:	Brass			IP Rating:	None	
Contact Finish:	Gold			Contact Material:	Phosphor Bronze	
Max. Freq.:	12.4 GHz			Contact Finish:	Gold	
Booting:	SMA Jack Straight RP			Max. Freq.:	11 GHz	
	3			Booting:	TNC Jack Right Angle	
				Clocking:	0°	



CONTROLLED DOCUMENT - DO NOT COPY

THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

SMA-ST-JK-RP/TNC-RA-JK G174 72I

Part No:

Q-710480003072I

UNLESS SPECIFIED TOLERANCE:

TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH

IS LESS THAN 12 INCHES