



POSTED PIN CONTACT (QTY = NO. OF POSN)  
 MAT'L: BRASS PER ASTM B16  
 FINSH: .000050 [0.00127] - .000150 [0.00381]  
 1PK GOLD PER ASTM B488, GRADE C, 10.000050 [0.000254] THK  
 OVER NICKEL PER QQ-N-290, .000150 [0.00381] THK

DIM	SIZE 1, 2, 4 CONTACT CONFIGURATION		SIZE 5 CONTACT CONFIGURATION	
	MIN	MAX	MIN	MAX
DIM T	1.96-2.10	2.30	2.83±.010	2.83±.010
DIM F	1.96-2.10	2.30	1.20	1.20
DIM G	1.96-2.10	2.30	1.20	1.20
DIM H	1.96-2.10	2.30	1.20	1.20
DIM I	1.96-2.10	2.30	1.20	1.20
DIM J	1.96-2.10	2.30	1.20	1.20
DIM K	1.96-2.10	2.30	1.20	1.20
DIM L	1.96-2.10	2.30	1.20	1.20
DIM M	1.96-2.10	2.30	1.20	1.20
DIM N	1.96-2.10	2.30	1.20	1.20
DIM O	1.96-2.10	2.30	1.20	1.20
DIM P	1.96-2.10	2.30	1.20	1.20
DIM Q	1.96-2.10	2.30	1.20	1.20
DIM R	1.96-2.10	2.30	1.20	1.20
DIM S	1.96-2.10	2.30	1.20	1.20
DIM U	1.96-2.10	2.30	1.20	1.20
DIM V	1.96-2.10	2.30	1.20	1.20
DIM W	1.96-2.10	2.30	1.20	1.20
DIM X	1.96-2.10	2.30	1.20	1.20
DIM Y	1.96-2.10	2.30	1.20	1.20
DIM Z	1.96-2.10	2.30	1.20	1.20

- U/CSA DESIGNATION STAMPED IN THIS AREA, OPTIONAL.
- THE FAR SIDE REFERS TO WIDE SIDE OF KEYSTONE.
- EPOXY IS APPLIED BETWEEN SHELLS AND INSERT AND ALL AROUND CONTACTS TO SEAL THE BACKSIDE OF THE ASSEMBLY FROM CONFORMAL COATING.

THIS DRAWING IS A CONTROLLED DOCUMENT

REVISIONS

REV	DATE	DESCRIPTION	BY	CHK
1	11-07-05	1883569-1		

DATE: 11-07-05

TIME: 10:00 AM

SCALE: 4:1

CUSTOMER DRAWING