



TAPE MTG DETAIL
 SCALE 2:1

- ① 0.76µm [.000030] MIN GOLD OVER 1.27µm [.000050] MIN NICKEL.
- 2. PLATING THICKNESS TO BE MEASURED ON SURFACES ACCESSIBLE WITH 0.64 [.025] DIA SPHERE.
- ③ WHEN ORDERING CONTACT ASSEMBLY ON TAPE, ORDER BY THE TAPE NUMBER PLUS THE PACKAGING CODE AS FOLLOWS:
 - 1. FOR USE WITH AMP TAPETRONIC, PNEUMATIC TOOL-
 - A. 1000 PARTS TO A BOX ADD PACKAGING CODE: 1MBOX
 - 2. FOR USE WITH 4/8 INDENT STRIPPER CRIMPER-
 - A. 1000 PARTS TO A REEL ADD PACKAGING CODE: 1MREEL
 - B. 5000 PARTS TO A REEL ADD PACKAGING CODE: 5MREEL
- ④ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

④ OBSOLETE	SMALL PACK	202507-3
④ OBSOLETE	TAPE MTG (SEE DETAIL) ③	202507-2
	STANDARD	202507-1
	PACKAGING TYPE	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	04/07/93	STE TE Connectivity
		CHK	4-26-93	
		APVD	4-29-93	NAME
				CONTACT ASSEMBY, PIN, #16, 16-18 AWG, TYPE II
DIMENSIONS: MM[INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED:		SIZE
		0 PLC ± -		CAGE CODE
		1 PLC ± -		DRAWING NO
		2 PLC ± -		RESTRICTED TO
		3 PLC ± -		
		4 PLC ± -		
		ANGLES ± ± -		
MATERIAL		FINISH		SCALE
PIN BODY: COPPER ALLOY		PIN BODY: ①		10:1
SPRING: STAINLESS STEEL		WEIGHT		SHEET
		CUSTOMER DRAWING		1 of 1
				REV
				F2

THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.