0.75 METER LENGTH



Connector A 112160 BNC Jack Straight Brass Nickel 50 Ohm RG-316 Continuity/Hi-Pot Connector B 000-69475 BNC Plug Straight Brass Nickel

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

Connector A			Cable			Connector B		
Contact Finish:	Part #:112160Description:BNC JK RG174Type:BNCGender:JackBody Type:StraightContact Type:SolderPolarity:StandardImpedance:50 OhmMounting:CableBody Material:BrassBody Finish:NickelIP Rating:NoneContact Material:Beryllium Coppet		RG316 LMR100 500 Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	Cable RG-316 RG-316 - ST 0.102 ST Braid 0.102 50 Ohm None Continuity Hi-Pot 0.75 Meter	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish:	Part #:000-69475Description:BNC Clamp PLUG RType:BNCGender:PlugBody Type:StraightContact Type:SolderPolarity:StandardImpedance:50 OhmMounting:CableBody Material:BrassBody Finish:NickelIP Rating:NoneContact Material:Brass		
Max. Freq.: Booting:	4 GHz BNC Jack Straigh	nt			Max. Freq.: Booting: Clocking:	4 GHz BNC Plug Straight 0°		
Amphenol CUSTOM CABLE		PROPRIETARY INFORMATION FOR ANY PURPOSE DETRIME INC. IT MAY NOT BE REPROD IN ANY FORM WITHOUT THE	S DRAWING MAY CONTAIN PATENTED OR PRIETARY INFORMATION AND MUST NOT BE USED ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE . IT MAY NOT BE REPRODUCED OR TRANSCRIBED NY FORM WITHOUT THE WRITTEN CONSENT OF FOOM CABLE DIC ACCEPTANCE OF THIS DRAWING		Title: BNC-ST-JK/BNC-ST-PL G316 0.75M		UNLESS SPECIFIED TOLERANCE: 0-18 inches +/ 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH	
CONTROLLED DOCUMENT - DO NOT COPY		CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.			Part No: Q-0300J0005.75M			



RoHS 2015/863 Compliance Statement

According to the manufacture of all the component parts contained in this assembly, this product has been determined to be RoHS Compliant with RoHS Directive 2011/65/EU and as amended by Directive 2015/863, and without material exceptions (RoHS3 Complaint).

For the individual component RoHS certificates used in this assembly, please contact Amphenol Custom Cable.

The RoHS Compliance of any product so designated is based upon evidence from the producer (manufacturers') that the component parts comply with the RoHS Directive. Amphenol Custom Cable has taken all reasonable steps to confirm that the OEM (Manufacturer) of the components used in this assembly have provided evidence regarding the absence of the restricted substances to support the manufacturer's claim of compliance.

To the best of our knowledge and with due diligence, we certify that the product listed herein complies with the RoHS requirements.

Date: 10/2/2023

Part Number: Q-0300J0005.75M

Manufacturer: Amphenol Custom Cable

Description: BNC-ST-JK/BNC-ST-PL G316 0.75M

This information is valid as of the date indicated for the item (part number) listed.

Director of Quality Assurance

Janice Frank