



Features

- Conductive Velostat® container
- Ideal for storage, kitting, and in-process handling of static-sensitive assemblies and devices
- Made from Velostat® injection-molded, conductive polypropylene
- Containers are noncorrosive and lightweight
- Conductive lid included

SPECIFICATIONS

Physical Properties

Property	Test Method	Value
Hardness	ASTM D2240	67-71 Shore D
Maximum Temp. Exposure		180°F
Tensile Strength	ASTM D638	2800 - 3000 psi
Flex Modulus	ASTM D790	13,000 - 150,000 psi

Electrical Properties

Volume Conductive	ASTM D991	<500 ohms/cm
Volume Resistance	ANSI/ESD STM11.12	<1 x 10 ⁴ ohms

Chemical Resistance	Reactions
Alcohol	Resistant
Aromatic Hydrocarbons	Severe Attack
Aliphatic Hydrocarbons	Moderate Attack
Concentrated Acids	Slight Attack
Concentrated Alkalines	Slight Attack
Kerosene	Severe Attack
Keytones (Acetone)	Moderate Attack
Mineral Oil	Slight Attack
Oil & Gasoline	Moderate Attack

Item	Size (Dia. x H)
57016*	2-3/8" x 7/8"
57017	1-13/16" x 4"
57018	3-13/16" x 4-11/16"

*Lid does not snap shut securely to container

Specifications and procedures subject to change without notice.



Made in the
United States of America

Unless otherwise noted tolerances are +/- 10%

CONDUCTIVE VELOSTAT® ROUND CONTAINER

PROTEKTIVE PAK

PROTEKTIVE PAK
 13250 MONTE VISTA AVENUE, CHINO, CA 91710
 PHONE (909) 627-2578
ProtektivePak.com

**DRAWING
NUMBER**
57018

DATE:
October
2019