



SHELL	A±0.38	B±0.12	C±0.10	D±0.25	E±0.07	LEAD FREE PART NUMBER
09	30.81	24.99	18.00	16.21	10.96	D09S80C4GV00
15	39.14	33.32	26.32	24.54	19.18	D15S80C6GV00
25	53.03	47.04	40.04	38.25	33.12	D25S80C8GV00
37	69.32	63.50	56.50	54.71	49.68	D37S80C8GV00

SHELL	A±0.38	B±0.12	C±0.10	D±0.25	E±0.07	LEAD FREE PART NUMBER
09	30.81	24.99	18.00	16.21	10.96	D09S80C4GV00LF
15	39.14	33.32	26.32	24.54	19.18	D15S80C6GV00LF
25	53.03	47.04	40.04	38.25	33.12	D25S80C8GV00LF
37	69.32	63.50	56.50	54.71	49.68	D37S80C8GV00LF

GENERAL CHARACTERISTICS AND ROHS INFORMATIONS:  
SEE DRAWING C01-8646-0001

mat'l. code		surface		tolerance		projection		product family	
lfr	ecn no	dr	date	ISO 1302	ISO 406	ISO 1001		D-SUB	
J	EX-17889	MP	2014/06/08	tolerance unless otherwise specified	±0.01	±0.01	MM	FEMALE CONNECTOR DELTA-D	
				angles	linear	scale 2:1		US RA PF	
				dr	PESSON	1995/10/31		dwg no	sheet 1 of 1
				engr	WITHUN PAUL	2014/06/06		C01-8646-0412	size
				chr	ALAS BABU	2014/06/06		Product Customer Drawing	A3
				appd	BLIU K PAUL	2014/06/06			
sheet index	revision	J	1						