TE Internal #: 1838275-4

Standard Circular Connectors, Wire-to-Wire, 8 Position, Sealable, Wire & Cable, Signal, Reverse Gender, A Polarization Code, PA,

Hermetically Sealed

View on TE.com >



Connectors > Circular Connectors > Standard Circular Connectors











Connector System: Wire-to-Wire

Number of Positions: 8

Sealable: Yes

Connector & Contact Terminates To: Wire & Cable

Contact Current Rating (Max): 2A

### **Features**

## Product Type Features

Assembly Requirement	Factory Assembled
Prewired	No
Assembly Type	Electrical Connector
Circular Connector Shell Type	All Plastic
Connector Product Type	Connector Assembly
Connector System	Wire-to-Wire
Connector System Sealable	Wire-to-Wire Yes
Sealable	Yes

### **Configuration Features**

Factory Installed Backshell	Without
Number of Positions	8
Number of Power Positions	0
Number of Signal Positions	4



Contacts Preloaded	Yes
Electrical Characteristics	
Operating Voltage	500 VAC
Body Features	
Environmental Protection Type	Sealed
Environmental Protection	With
Circular Connector Insulation Material Type	PA
Hermetically Sealed	Yes
Contact Features	
Contact Current Rating (Max)	2 A
Reverse Gender	Yes
Circular Connector Contact Type	Pin
Mechanical Attachment	
Polarization Code	A
Mating Alignment Type	1 Key
Mating Retention	With
Housing Features	
Circular Connector Shell Size	15
Dimensions	
Wire Size	$.345 \text{ mm}^2$
Usage Conditions	
Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]
Operation/Application	
Circuit Application	Signal
Shielded	No
Packaging Features	
Packaging Quantity	20
Other	
Field Serviceable	Yes

# **Product Compliance**



#### For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Hand solderable with lead free solder

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts





# Customers Also Bought





















#### **Documents**

## **Product Drawings**

M12 Fld Ser CONN. Male Pin Sldr

English

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1838275-4\_B.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1838275-4\_B.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1838275-4\_B.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Standard Circular Connectors, Wire-to-Wire, 8 Position, Sealable, Wire & Cable, Signal, Reverse Gender, A Polarization Code, PA, Hermetically Sealed



M8 / M12 Connector System Catalog

English

M8 / M12 Connector System Catalog

Japanese

**Product Specifications** 

**Product Specification** 

English