

1624075

https://www.phoenixcontact.com/us/products/1624075

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M23, Cable connector, series: CA, angled, shielded: yes, Screw locking mechanism, No. of pos.: 16+2+FE, Direction of rotation: Standard, contact connection type: Pin, Crimp connection, cable diameter range: 3 mm ... 14.5 mm, coding: N, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1245086

### Your advantages

- · Angled cable outlet for confined spaces
- · Can be adapted to various applications, thanks to adjustable cable outlet direction
- · Safe use in the field, thanks to high degree of protection
- · Connector for flexible on-site assembly
- · Consistent EMC protection for reliable transmission of signals
- · Crimping connection: vibration- and temperature-resistant assembly

### Commercial data

Item number	1624075
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	AB33
Product key	ABRAEC
Catalog page	Page 93 (C-2-2019)
GTIN	4055626230665
Weight per piece (including packing)	187.7 g
Weight per piece (excluding packing)	140.735 g
Customs tariff number	85366990
Country of origin	DE



1624075

https://www.phoenixcontact.com/us/products/1624075

### Technical data

#### Notes

	General	Order crimp contacts 16 x Ø 1 mm, 2 x Ø 1.5 mm, 1 x Ø 1.5 (PE) separately			
Product properties					
	Product type	Circular connector (cable-side)			

#### Connector

#### Insulating body

Note	Order information: Order crimp contacts 16x Ø 1 mm, 2x Ø 1. 5 mm, 1x Ø 1.5 mm (FE, first) separately
Coding	N
Insulation body material	PA 6.6
Connection method	Crimp connection
Contact switching type	Pin
Application	Signal
Number of positions	19
Direction of rotation	Standard
Connection profile	16+2+FE
Contact diameter Power contacts	1.5 mm
Litz wire cross-section Power contacts min.	0.08 mm²
Litz wire cross-section Power contacts max.	1 mm²
Rated current Power contacts	10 A
Note	for max. connection cross section
Rated voltage	48 V AC
	74 V DC
Rated surge voltage	1.5 kV
Overvoltage category	III
Degree of pollution	3
Contact diameter Signal contacts	1 mm
Litz wire cross-section Signal contacts min.	0.08 mm²
Litz wire cross-section Signal contacts max.	1 mm²
Nominal current per signal contact	8 A
Rated voltage Signal contact	48 V AC
Rated surge voltage	1.5 kV
Overvoltage category	III
Degree of pollution	3

Housing



1624075

https://www.phoenixcontact.com/us/products/1624075

Housing material	Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)			
Type of locking	Screw locking mechanism			
Pg screw connection	none			
Degree of protection (plugged in)	IP67			
Thread type	M23			
Seal				
External cable diameter	3 mm 14.5 mm			
Seal material	NBR			




1624075

https://www.phoenixcontact.com/us/products/1624075

### Drawings

### Dimensional drawing




Dimensional drawing



1624075

https://www.phoenixcontact.com/us/products/1624075

### Schematic diagram



Connector pin assignment



1624075

https://www.phoenixcontact.com/us/products/1624075

### Classifications

UNSPSC 21.0

### **ECLASS**

ECLASS-11.0	27440102			
ECLASS-12.0	27440116			
ECLASS-13.0	27440116			
ETIM				
ETIM 8.0	EC002635			
UNSPSC				

39121400



1624075

https://www.phoenixcontact.com/us/products/1624075

## Environmental product compliance

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"



1624075

https://www.phoenixcontact.com/us/products/1624075

#### Accessories

RC-15P2010 - Crimp contact

1623776

https://www.phoenixcontact.com/us/products/1623776



Crimp contact, Pin, turned, contact diameter: 1 mm, crimp range:  $0.08 \text{ mm}^2 \dots 0.22 \text{ mm}^2$ , Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1244971

### RC-15P2020 - Crimp contact

1623777

https://www.phoenixcontact.com/us/products/1623777



Crimp contact, Pin, turned, contact diameter: 1 mm, crimp range:  $0.14~\text{mm}^2$  ...  $0.56~\text{mm}^2$ , Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1244971



1624075

https://www.phoenixcontact.com/us/products/1624075

### RC-15P2030 - Crimp contact

1623778

https://www.phoenixcontact.com/us/products/1623778



Crimp contact, Pin, turned, contact diameter: 1 mm, crimp range:  $0.5 \text{ mm}^2 \dots 1 \text{ mm}^2$ , Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1244972

#### RC-15P2200 - Crimp contact

1627292

https://www.phoenixcontact.com/us/products/1627292



Crimp contact, Pin, turned, contact diameter: 1.5 mm, crimp range:  $0.08~\text{mm}^2$  ...  $0.22~\text{mm}^2$ , Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1245475



1624075

https://www.phoenixcontact.com/us/products/1624075

### RC-15P2300 - Crimp contact

1627291

https://www.phoenixcontact.com/us/products/1627291



Crimp contact, Pin, turned, contact diameter: 1.5 mm, crimp range: 0.14 mm $^2$  ... 0.56 mm $^2$ , Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1245475

### RC-15P2000 - Crimp contact

1623779

https://www.phoenixcontact.com/us/products/1623779



Crimp contact, Pin, turned, contact diameter: 1.5 mm, crimp range:  $0.5~\text{mm}^2$  ... 1 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1244973



1624075

https://www.phoenixcontact.com/us/products/1624075

### RC-15P2100 - Crimp contact

1623780

https://www.phoenixcontact.com/us/products/1623780



Crimp contact, Pin, leading, turned, contact diameter: 1.5 mm, crimp range:  $0.5 \, \text{mm}^2 \dots 1 \, \text{mm}^2$ , Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1244974

#### RC-Z2058 - Protective cap

1604223

https://www.phoenixcontact.com/us/products/1604223



Plastic protection cap for connectors with M23 knurled nut



1624075

https://www.phoenixcontact.com/us/products/1624075

### RC-Z2468 - Protective cap

1611796

https://www.phoenixcontact.com/us/products/1611796



Plastic protection cap, antistatic, for connectors with M23 knurled nut

### RF-Z0014 - Color-coding

1620588

https://www.phoenixcontact.com/us/products/1620588

Color-coding, color: green





1624075

https://www.phoenixcontact.com/us/products/1624075

RF-Z0015 - Color-coding

1620592

https://www.phoenixcontact.com/us/products/1620592

Color-coding, color: orange



RF-Z0016 - Color-coding

1620593

https://www.phoenixcontact.com/us/products/1620593

Color-coding, color: black





1624075

https://www.phoenixcontact.com/us/products/1624075

### RF-Z0003 - Square mounting flange

1607905

https://www.phoenixcontact.com/us/products/1607905



Square mounting flange, Axial seal, 4xM3, flange dimensions: 35 mm x 35 mm, series: RF, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1242369

### SF-Z0028 - Torque screwdriver

1607456

https://www.phoenixcontact.com/us/products/1607456



Torque screwdriver, series: RC



1624075

https://www.phoenixcontact.com/us/products/1624075

#### SF-Z0027 - Hook wrench

1607455

https://www.phoenixcontact.com/us/products/1607455



Hook wrench, series: RC

### RF-Z0007 - Special wrench

1614347

https://www.phoenixcontact.com/us/products/1614347

Special wrench, series: RF



Phoenix Contact 2023 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com