

Data sheet | Item number: 709-170

Disconnect lock; for disconnect tab used on 280/281 and 769 Series
disconnect terminal blocks; red

www.wago.com/709-170



Data

Material Data

Note (material data)

Information on material specifications can be found here

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Color	red
Fire load	0.023 MJ
Weight	0.8 g

Commercial data

Product Group	2 (Terminal Block Accessories)
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 8.0	EC002848
ETIM 7.0	EC002848
PU (SPU)	200 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4017332812412
Customs tariff number	39269097900

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Documentation

Bid Text

709-170 X81 - Datei	2019 年2月19 日	xml 2.6 kB	Download
709-170 doc - Datei	2017 年4月28 日	doc 23.6 kB	Download

Additional Information

		pdf 2.2 MB	Download
--	--	---------------	----------

CAD/CAE-Data

CAE data

WSCAD Universe 709-170		URL	Download
------------------------	--	-----	----------

Subject to changes. Please also observe the further product documentation!



CAD data

2D/3D Models 709-170	URL	Download
----------------------	-----	----------

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 709-170	URL	Download
--	-----	----------

Disconnect lock; for disconnect tab used on 280/281 and 769 Series disconnect terminal blocks; red

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Double Safety:

The disconnect tab has been designed for maximum operational safety.

As soon as the disconnect tab is in the disconnect position, it can be protected against unintentional reconnection by using the disconnect lock.

Only through intentional and deliberate use of a tool, can the disconnect lock be removed and the circuit reconnected.

Features/Benefits:

- Easy to use
- Install/remove disconnect lock with just one hand
- Clearly identify disconnect tab position
- Higher safety
- Intentional effort is required to reconnect the circuit

Installation


Subject to changes. Please also observe the further product documentation!



Installing a disconnect lock on the terminal block's disconnect tab.



Unlocking a disconnect lock.



Removing a disconnect lock.

Subject to changes. Please also observe the further product documentation!