



- NOTES:**
1. Waterproof rate: IP67
 2. Gasket: EPDM Black
 3. Housing: ABS Black
 4. Screw: Brass
 5. O-ring: Silicone Clear
 6. Body: Nylon Black
 7. Sealing Nut: Nylon Black
 8. Connector: D-Sub 15Pin Female, pin in full gold plated
 9. Seals for Cable OD: $\phi 6.0\text{mm} - \phi 10.0\text{mm}$
 10. One Set Unassembled in One Zipper Bag

ROHS compliant
Unit: mm

| Scale | Free |
|-----------|------|
| TOLERANCE | |
| UNIT | ±0.5 |
| DIM | TOL |
| Angle | TOL |

| Id. | Modification | Date | Name |
|-----|--------------------------------------|------------|--------|
| ① | Cancel "A" logo & correct dimensions | 03.04.2018 | Amy |
| ② | Drawn | 22.04.2014 | Joanna |

| Customer-No. | Date | Name |
|-----------------|------------|--------|
| ASSMANN WSW-No. | 22.04.2014 | Joanna |
| A-DF15-HOOD-WP | 03.04.2018 | Amy |

| Drawing-No. | Replace | Sheet |
|-------------|------------------------|-------|
| ASS 6256 CO | ASSMANN WSW components | rev01 |

| | | | | | | |
|---|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 |
| A | B | C | D | E | F | G |