



In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD		TEST METHOD		REQUIREMENTS		QT	AT
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C ⁽¹⁾	STORAGE TEMPERATURE RANGE	-10 °C TO 60 °C ⁽²⁾			
	VOLTAGE	125 V AC	OPERATING HUMIDITY RANGE	40 % TO 80 %			
	CURRENT	0.5 A	STORAGE HUMIDITY RANGE	40 % TO 70 % ⁽²⁾			
SPECIFICATIONS							
ITEM	TEST METHOD		REQUIREMENTS		QT	AT	
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.		X	X	
MARKING		CONFIRMED VISUALLY.			X	X	
ELECTRIC CHARACTERISTICS							
CONTACT RESISTANCE	100 mA (DC OR 1000 Hz).		45 mΩ MAX.		X	-	
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD	20 mV MAX, 1 mA(DC OR 1000Hz)		55 mΩ MAX.		X	-	
INSULATION RESISTANCE	250 V DC		100 MΩ MIN.		X	-	
VOLTAGE PROOF	300 V AC FOR 1 min.		NO FLASHOVER OR BREAKDOWN.		X	-	
MECHANICAL CHARACTERISTICS							
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.		INSERTION FORCE:	35.2 N MAX.	X	-	
MECHANICAL OPERATION	500 TIMES INSERTIONS AND EXTRactions.		WITHDRAWAL FORCE:	4.0N MIN.	X	-	
VIBRATION	FREQUENCY 10 TO 55 Hz, AMPLITUDE : 1.52 mm, AT 2h FOR 3 DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 1 μs.		X	-	
SHOCK	490 ms ² , DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.		② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	-	
ENVIRONMENTAL CHARACTERISTICS							
DAMP HEAT (STEADY STATE)	EXPOSED AT 40±2 °C, 90 ~ 95 %, 96 h.		① CONTACT RESISTANCE: 55 mΩ MAX.		X	-	
RAPID CHANGE OF TEMPERATURE	TEMPERATURE:-55→+15~+35→+85→+15~+35°C TIME 30 → 10~15 → 30 → 10~15 min. UNDER 5 CYCLES.		② INSULATION RESISTANCE:100 MΩ MIN.		X	-	
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.		③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	-	
HYDROGEN SULPHIDE	EXPOSED IN 3 PPM FOR 96 h. (TEST STANDARD: JEIDA 38)		① CONTACT RESISTANCE: 55 mΩ MAX.		X	-	
RESISTANCE TO SOLDERING HEAT	1) SOLDER BATH:SOLDER TEMPERATURE, 260±5°C FOR IMMERSION DURATION,10±1s.		② NO HEAVY CORROSION.		X	-	
SOLDERABILITY	2) SOLDERING IRONS : 360°C FOR 5 s. SOLDERED AT SOLDER TEMPERATURE, 240±3°C, FOR IMMERSION DURATION, 2 s.		NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.		X	-	
			A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSED.		X	-	
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE			
REMARK	⁽¹⁾ TEMPERATURE RISE INCLUDED WHEN ENERGIZED						
	⁽²⁾ THIS STORAGE INDICATES A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE THE BOARD MOUNTED.						
	APPROVED		HS. OKAWA		07.06.19		
	CHECKED		HS. OZAWA		07.06.19		
DESIGNED		SY. KAMIIGA		07.06.19			
DRAWN		HK. SUMADORI		07.06.18			
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.		ELC4-083221-21			
		SPECIFICATION SHEET		PART NO.		FX202-40S-1. 27DSAL (71)	
		HIROSE ELECTRIC CO., LTD.		CODE NO.		GL572-2473-8-71	
						 1/1	