



Bestückungsplan - contact layout



■ = bestückt - assemble

Lochbild für Leiterplatte Board hole pattern (Component mounting side)



1)  $\varnothing 0,6 \pm 0,05$  Durchmesser des metallisierten Loches  
 $\varnothing 0,6 \pm 0,05$  Diameter of finished plated-through hole

$\varnothing 0,7 \pm 0,02$  Bohrungsdurchmesser des Loches  
 $\varnothing 0,7 \pm 0,02$  Diameter of drilled hole

Schichtaufbau im metallisierten Loch  
 siehe Zeichnung 114406

Metal plating of plated-through hole  
 see drawing 114406

Bedruckung siehe Zeichnung 284811  
 Marking see drawing 284811

Fehlende Masse und Angaben nach IEC 61076-4-101  
 Missing information and dimensions per IEC 61076-4-101

Information : Abschirmbleche Reihe z+i montiert shieldings row z+i mounted	Tolerances	Scale 2:1
	All Dimensions in mm	
All rights reserved. Only for information. To insure that this is the latest version of this drawing, please contact one of the ERNI companies before using.	Subject to modification without prior notice. Drawing will not be updated.	Designation
		ERmet-FS Federleiste E ERmet-Female Straight Type E
ERNI	www.ERNI.com	124096
b	11.03.2008	i
Index	Date	H:00065161.SZA
		ERME

Consider protection memo from DIN 34