

### Features

- Low  $V_{ce(sat)}$ , Fast Switching
- $V_{ce(sat)}$  with Positive Temperature Coefficient
- High Ruggedness, Good Thermal Stability
- Very Tight Parameter Distribution
- Halogen Free
- Epoxy Meets UL 94 V-0 Flammability Rating
- Lead Free Finish/RoHS Compliant ("P" Suffix Designates RoHS Compliant. See Ordering Information)

### Maximum Ratings


- Operating Junction Temperature Range : -55°C to +150°C
- Storage Temperature Range: -55°C to +150°C
- IGBT Thermal Resistance: 0.45°C/W Junction to Case
- Diode Thermal Resistance: 0.8°C/W Junction to Case
- Thermal Resistance: 40°C/W Junction to Ambient

Parameter	Symbol	Rating	Unit
Collector-Emitter Voltage	$V_{CE}$	1200	V
DC Collector Current <sup>(1)</sup>	$I_C$	$T_C=25^\circ\text{C}$	80
		$T_C=100^\circ\text{C}$	40
Pulsed Collector Current <sup>(2)</sup>	$I_{C,pluse}$	160	A
Diode Forward Current <sup>(1)</sup>	$I_F$	$T_C=25^\circ\text{C}$	40
		$T_C=100^\circ\text{C}$	20
Diode Pulsed Current <sup>(2)</sup>	$I_{F,pluse}$	160	A
Gate-Emitter Voltage	$V_{GE}$	$\pm 20$	V
Short Circuit Withstand Time <sup>(3)</sup> $V_{GE}=15\text{V}, V_{CC}=600\text{V}, T_J \leq 150^\circ\text{C}$	$t_{SC}$	10	$\mu\text{s}$
Power Dissipation	$P_D$	$T_C=25^\circ\text{C}$	277
		$T_C=100^\circ\text{C}$	111

Note:


1. Limited by  $T_{Jmax}$ .
2.  $T_p$  limited by  $T_{Jmax}$ .
3. Allowed number of short circuits: <1000; time between short circuits: >1s.

### Internal Structure



# Trench and Field Stop IGBT 1200V 40A

TO-247



DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.787	0.866	20.00	22.00	
B	0.598	0.638	15.20	16.20	
C	0.185	0.208	4.70	5.30	
D	0.035	0.059	0.90	1.50	
E	0.059	0.094	1.50	2.40	
F	0.067	0.091	1.70	2.30	
J	0.019	0.031	0.48	0.80	
K	0.748	0.833	19.00	21.15	
P	0.122	0.189	3.10	4.80	
Q	0.118	0.150	3.00	3.80	$\Phi$
V	0.106	0.134	2.70	3.40	
G	0.197	0.224	5.00	5.70	

**Electrical Characteristics @ 25°C (Unless Otherwise Specified)**

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
<b>Static Characteristics</b>						
Collector-Emitter Breakdown Voltage	$V_{(BR)CES}$	$V_{GE}=0V, I_C=0.25mA$	1200			V
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$V_{GE}=15V, I_C=40A$		1.9	2.4	V
		$V_{GE}=15V, I_C=40A, T_J=150^\circ C$		2.3		
Diode Forward Voltage	$V_F$	$V_{GE}=0V, I_F=20A$		2.45		V
		$V_{GE}=0V, I_F=20A, T_J=150^\circ C$		1.9		
G-E Threshold Voltage	$V_{GE(th)}$	$I_C=1mA, V_{CE}=V_{GE}$	5.5	6	6.5	V
C-E Leakage Current	$I_{CES}$	$V_{CE}=1200V, V_{GE}=0V$			0.1	mA
		$V_{CE}=1200V, V_{GE}=0V, T_J=150^\circ C$			4	
G-E Leakage Current	$I_{GES}$	$V_{CE}=0V, V_{GE}=20V$			250	nA
Transconductance	$g_{FS}$	$V_{CE}=20V, I_C=40A$		26.5		S
<b>Dynamic Characteristics</b>						
Input Capacitance	$C_{ies}$	$V_{CE}=25V, V_{GE}=0V, f=1MHz$		3823		pF
Output Capacitance	$C_{oes}$			170		
Reverse Transfer Capacitance	$C_{res}$			94		
Gate Charge	$Q_g$	$V_{CC}=600V, I_C=40A, V_{GE}=15V$		239		nC
<b>IGBT Switching Characteristics</b>						
Turn-On Delay Time	$t_{d(on)}$	$V_{CC}=600V, I_C=40A, V_{GE}=0/15V, R_G=10\Omega, \text{ Inductive load}$		62		ns
Rise Time	$t_r$			54		
Turn-Off Delay Time	$t_{d(off)}$			265		
Fall Time	$t_f$			30		
Turn-On Energy	$E_{on}$			3.3		mJ
Turn-Off Energy	$E_{off}$			1.4		
Total Switching Energy	$E_{ts}$			4.7		
Turn-On Delay Time	$t_{d(on)}$	$V_{CC}=600V, I_C=40A, V_{GE}=0/15V, R_G=10\Omega, T_J=150^\circ C, \text{ Inductive load}$		55		ns
Rise Time	$t_r$			55		
Turn-Off Delay Time	$t_{d(off)}$			306		
Fall Time	$t_f$			38		
Turn-On Energy	$E_{on}$			3.49		mJ
Turn-Off Energy	$E_{off}$			1.85		
Total Switching Energy	$E_{ts}$			5.34		

**Electrical Characteristics @ 25°C (Unless Otherwise Specified)**

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
<b>Diode Characteristics</b>						
Reverse Recovery Time	$t_{rr}$	$V_R=600V, I_F=20A,$ $di_F/dt=100A/\mu s$		80		ns
Reverse Recovery Charge	$Q_{rr}$			0.15		$\mu C$
Peak Reverse Recovery Current	$I_{rrm}$			5.4		A

**Curve Characteristics**

Fig. 1 - FBSOA




Fig. 2 - RBSOA




Fig. 3 - Typical Output Characteristics




Fig. 4 - Typical Output Characteristics




Fig. 5 -  $V_{CE(sat)} - I_C$





Fig. 6 -  $V_{CE(sat)} - T_C$



## Curve Characteristics

Fig. 7 - Gate Charge




Fig. 8 - Capacitance Characteristics




Fig. 9 - Power Derating Curve





Fig. 10 - Collector Current Derating Curve



## Ordering Information

Device	Packing
Part Number-BP	Tube:30pcs/Tube, 360pcs/Box, 1.8K/Ctn;

Note : Adding "-HF" Suffix For Halogen Free, eg. Part Number-BP-HF

### \*\*\*IMPORTANT NOTICE\*\*\*

*Micro Commercial Components Corp.* reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . *Micro Commercial Components Corp.* does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp.* and all the companies whose products are represented on our website, harmless against all damages. *Micro Commercial Components Corp.* products are sold subject to the general terms and conditions of commercial sale, as published at <https://www.mccsemi.com/Home/TermsAndConditions>.

### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.