



PCB LAYOUT
(TopView)

Specification:

1. Electrical Char

Insulation Resistance: 500MΩ min. 500V DC
for 1 minute

Contact Resistance: 30mΩ max.

Rating Current: 1.5A max.

Rating Voltage: 150V AC

Dielectric Voltage: 1000 Vrms at 1MA 60 sec. min.

2. Physical Char

Housing: PBT Glass filled (UL 94V-0) Color: Black

Soldering Temperature: 235°C for 5 sec.

Spring Wire: 0.35mm Dia Phosphor Bronze

6u" Gold plating over Nickel

Temperature Range: -40°C to +85°C

Durability: 750 mating cycles min.

3. Packing: Tray

RoHS compliant
Unit:mm

Scale	Free						Date	Name	Customer-No.
TOLERANCE							Drawn	04.08.2016	Winnie
.XX	±0.20						Approved	17.06.2019	Winnie
.XXX	±0.13								
.XXXX	±0.05								
DIM	TOL	①	Update the dimension	17.06.2019	Segal				
		②	Drawn	04.08.2016	Winnie				
Angle	+0°30'	Id.	Modification	Date	Name				

Customer-No.			
ASSMANN WSW-No.		A-2004-2-4-N-R	
Drawing-No.		ASS 7324 CO	
Replace		rev01	
		SHEET	