# Product data sheet Characteristics

# ZCKE215

Limit switch head, Limit switches XC Standard, ZCKE, thermoplastic roller lever plunger, +120 °C





#### Main

Main	
Range of Product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or Component Type	Limit switch head
Device short name	ZCKE
Head type	Plunger head
Product Compatibility	XCKJ
Associated body	ZCKJD37H29 ZCKJ11 ZCKJ5H7 ZCKJD39H29 ZCKJ2H7 ZCKJ5H29 ZCKJ1H7 ZCKJD39H7 ZCKJD39H7 ZCKJD35H7 ZCKJD31H7 ZCKJD31H7 ZCKJD31H29 ZCKJB429 ZCKJB429 ZCKJB35 ZCKJ6 ZCKJ6 ZCKJ6 ZCKJ6 ZCKJ6 ZCKJ6 ZCKJ1H7 ZCKJ41 ZCKJ37H7 ZCKJ41 ZCKJ21H7 ZCKJ41 ZCKJ21H7 ZCKJ34 ZCKJ21H7 ZCKJ34 ZCKJ21H7 ZCKJ34 ZCKJ21H7 ZCKJ34 ZCKJ21H29 ZCKJ34 ZCKJ21H29 ZCKJ4H29 ZCKJB37H7 ZCKJ4H29 ZCKJB39 ZCKJB39 ZCKJB39 ZCKJB4H7 ZCKJB1 ZCK
Movement of operating head	Linear
Type of operator	Roller lever plunger spring return thermoplastic
Type of approach	Lateral approach, 1 direction

# Complementary

Switch actuation	By 30° cam
Positive opening	With
Net Weight	0.41 lb(US) (0.185 kg)
Head material	Metal

### Environment

Ambient Air Temperature for Operation	50248 °F (10120 °C)
Ambient Air Temperature for Storage	50248 °F (10120 °C)
Environmental characteristic	High temperature

### Ordering and shipping details

LIMIT SWITCHES,IEC,XCKJ 0325393
0325393
0325393
s) (0.45 kg)

## Packing Units

Package 1 Height	0.060 dm
Package 1 width	0.044 dm
Package 1 Length	0.055 dm

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	<sup>™</sup> REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₽¥Yes
Environmental Disclosure	Product Environmental Profile

### Contractual warranty

Warranty	18 months