

THIS DRAWING IS UNPUBLISHED.		RELEASED FOR PUBLICATION		LOC		DIST		REVISIONS					
© COPYRIGHT - By Tyco Electronics Japan G.K.		ALL RIGHTS RESERVED.		J				P	LTR	DESCRIPTION	DATE	DWN	APVD
PART NUMBER	QTY	IZUMI P/N		REMARKS		WEIGHT (Approx.) 質量 (約)		A2		ECR-11-021949 -7 OBSOLETE	31OCT2011	S.N	J.K
2155365-1	1	No.1 head	1号ヘッド	1.25~5.5mm ²	Non-insulated 裸圧着端子、スリーブ	△2	350g						
2155365-2	1	No.3 head	3号ヘッド	1.25mm ²	Insulated 絶縁被覆付圧着端子、スリーブ	△2	395g						
2155365-3	1	No.4 head	4号ヘッド	2mm ²	Insulated 絶縁被覆付圧着端子、スリーブ	△2	405g						
2155365-4	1	No.5 head	5号ヘッド	5.5mm ²	Insulated 絶縁被覆付圧着端子、スリーブ	△2	400g						
2155365-5	1	No.7A head	7号Aヘッド	CE-2, CE-5	Closed end 絶縁被覆付閉端接続子	△3	365g						
2155365-6	1	No.8 head	8号ヘッド	CE-1, CE-8	Closed end 絶縁被覆付閉端接続子	△3	370g						



-1 AS SHOWN



-2 AS SHOWN



-3 AS SHOWN



-4 AS SHOWN



-5 AS SHOWN



-6 AS SHOWN

NOTE

1. このダイスは 2155364-1 TE AC-5N-D PNEUMATIC CRIMPING TOOL 用です。
THIS DIES FOR 2155364-1 TE AC-5N-D PNEUMATIC CRIMPING TOOL.

△2 JIS C 2805 (銅線用裸圧着端子、銅線用絶縁被覆付圧着端子)、
JIS C 2806 (銅線用裸圧着スリーブ) に基づく圧着接続用。
TE 製の端子には適用していません。

For the crimp terminals of JIS C 2805 and JIS C 2806.
(JIS: Japanese Industrial Standards)
It has not applied to the TE terminal.

△3 JIS C 2807 (絶縁被覆付閉端接続子) に基づく圧着接続用。
TE 製の端子には適用していません。

For the crimp terminals of JIS C 2807.
(JIS: Japanese Industrial Standards)
It has not applied to the TE terminal.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	S.NAKA	11SEP2011	TE Connectivity
		CHK	S.NAKA	11SEP2011	
		APVD	J.KOGA	11SEP2011	
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME	
		0 PLC	± -	PRODUCT SPEC	
		1 PLC	± -	APPLICATION SPEC	
		2 PLC	± -	-	
		3 PLC	± -	-	
		4 PLC	± -	-	
		ANGLES	± -	-	
MATERIAL	-	FINISH	-	WEIGHT	-
		CUSTOMER DRAWING		SIZE	A3
				CAGE CODE	00779
				DRAWING NO	C-2155365
				RESTRICTED TO	-
				SCALE	-
				SHEET	1 OF 1
				REV	A2