



Insulated cross-connector, No. of poles: 3, Mounting type: Plug in, Width: 22.4 mm, Rated cross-section: 6 mm², Colour: Yellow

RAL: 1026

Business data

Article number	<u>17222.8</u>
Article name	SQI 6/3 YE
GTIN (EAN)	4044211148751
Packaging unit	50
Quantity unit	PC
Weight per piece (not including packaging)	3.3 g
Weight per piece (including packaging)	3.34 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Prio-Article	17222.8
Product description	Insulated cross-connector



Technical data

Dimensions		
Length	4 mm	
Width	22.4 mm	
Height	23 mm	
Pitch size	8 mm	
Ratings		
Voltage with partition, max.	1000 V	
Voltage without partition, max.	1000 V	
Rated current	41 A	
Current load, max.	41 A	
Rated cross-section	6 mm ²	
Contamination degree	2	
Connection data		
No. of poles	3	
Materials		
Material	Copper alloy	
Insulation housing	Polyamide 6.6	
Flammability class UL 94	V-2	
Working temperature, min.	-40 °C	
Working temperature, max.	105 °C	
Further technical data		
Mounting type	Plug in	
Insulation available	\checkmark	
Touch protection is available	\checkmark	
Number of bridged terminals	3	
Environmental Product Compliance		
REACH Conform	Yes	
REACH Candidate Substance Note	No	
RoHS Conform	Yes	

Media





Accessories

Insulation cap for cross-connector

Insulating cap,	Colour: Yellow		
Article number	Article name	GTIN (EAN)	Packaging unit
17200.8	SQIK 2,5-10 YE	4044211148539	20

##INVERSE##CONTA-CONNECT

Test disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17523.2	SPTK 6/LT/HB BG	4044211209223	50 ST



Test disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17524.2	SPTK 6/LT/STBI/YE BG	4044211209919	50 ST

Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
17151.4	SSIK 6/2A BK	4044211188993	50 ST



Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
17176.4	SSIK 6/2A/LED 30-60V AC/DC BK	4044211188931	50 ST



Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
17178.4	SSIK 6/2A/LED 500V AC/DC BK	4044211188948	50 ST



##INVERSE##CONTA-CONNECT

			ur: Beige	
	Article number	Article name	GTIN (EAN)	Packaging unit
	17520.2	SPTK 6/DU BG	4044211209650	50 ST
		ct terminal, Screw connection, Mour ection: 6 mm², Width: 8.1 mm, Colou	• • •	I TS 35/7.5,
	Article number	Article name	GTIN (EAN)	Packaging unit
	17521.2	SPTK 6/LT BG	4044211209162	50 ST
41- 1 -1-		ct terminal, Screw connection, Mour ection: 6 mm², Width: 8.1 mm, Colou	• • •	I TS 35/7.5,
	Article number	Article name	GTIN (EAN)	Packaging unit
	17522.2	SPTK 6/QT BG	4044211209216	50 ST
		ct terminal, Screw connection, Mour ection: 6 mm ² , Width: 8.1 mm, Colou Article name	• • •	Packaging
				unit
	17525.2	SPTK 6/LT/STBI/BU BG	4044211209926	unit 50 ST
	Fuse-disconne	SPTK 6/LT/STBI/BU BG ect terminal, Screw connection, Mou ection: 6 mm ² , Width: 8.1 mm, Colou Article name	inting type: Mounting ra	50 ST
	Fuse-disconne Rated cross-se	ect terminal, Screw connection, Mou ection: 6 mm², Width: 8.1 mm, Colou	inting type: Mounting ra ur: Black	50 ST il TS 35/7.5, Packaging
	Fuse-disconne Rated cross-se Article number <u>17175.4</u> Fuse-disconne	ect terminal, Screw connection, Mou ection: 6 mm², Width: 8.1 mm, Colou Article name	Inting type: Mounting ra ur: Black GTIN (EAN) 4044211188924 Inting type: Mounting ra	50 ST il TS 35/7.5, Packaging unit 50 ST
	Fuse-disconne Rated cross-se Article number <u>17175.4</u> Fuse-disconne	ect terminal, Screw connection, Mou ection: 6 mm ² , Width: 8.1 mm, Colou Article name SSIK 6/2A/LED 12-30V AC/DC BK ect terminal, Screw connection, Mou	Inting type: Mounting ra ur: Black GTIN (EAN) 4044211188924 Inting type: Mounting ra	50 ST il TS 35/7.5, Packaging unit 50 ST il TS 35/7.5,
	Fuse-disconne Rated cross-se Article number <u>17175.4</u> Fuse-disconne Rated cross-se	ect terminal, Screw connection, Mou ection: 6 mm ² , Width: 8.1 mm, Colou Article name SSIK 6/2A/LED 12-30V AC/DC BK ect terminal, Screw connection, Mou ection: 6 mm ² , Width: 8.1 mm, Colou	anting type: Mounting ra ur: Black GTIN (EAN) 4044211188924 Inting type: Mounting ra ur: Black	50 ST il TS 35/7.5, Packaging unit 50 ST il TS 35/7.5, Packaging
	Fuse-disconne Rated cross-se Article number 17175.4 Fuse-disconne Rated cross-se Article number 17177.4 Protective eart	ect terminal, Screw connection, Mou ection: 6 mm ² , Width: 8.1 mm, Colou Article name SSIK 6/2A/LED 12-30V AC/DC BK ect terminal, Screw connection, Mou ection: 6 mm ² , Width: 8.1 mm, Colou Article name	anting type: Mounting ra GTIN (EAN) 4044211188924 Unting type: Mounting ra ur: Black GTIN (EAN) 4044211188955 hting type: Mounting rai	50 ST il TS 35/7.5, Packaging unit 50 ST il TS 35/7.5, Packaging unit 50 ST
	Fuse-disconne Rated cross-se Article number 17175.4 Fuse-disconne Rated cross-se Article number 17177.4 Protective eart	ect terminal, Screw connection, Mou ection: 6 mm ² , Width: 8.1 mm, Colou Article name SSIK 6/2A/LED 12-30V AC/DC BK ect terminal, Screw connection, Mou ection: 6 mm ² , Width: 8.1 mm, Colou Article name SSIK 6/2A/LED 110-250V AC/DC BK	anting type: Mounting ra GTIN (EAN) 4044211188924 Unting type: Mounting ra ur: Black GTIN (EAN) 4044211188955 hting type: Mounting rai	50 ST il TS 35/7.5, Packaging unit 50 ST il TS 35/7.5, Packaging unit 50 ST



##INVERSE##CONTA-CONNECT



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 8 mm, Colour: Black-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
17132.2	SRK 6/2A/PE BKYE	4044211200718	100 ST



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17109.2	SRK B 6/2A BG	4044211141745	100 ST



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17108.2	SRK 6/2A BG	4044211141738	100



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17110.2	SRK 6/2A/Z BG	4044211141752	100 ST



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17117.2	SRK 6/2A SAS BG	4044211149000	80



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
87805.2	SRK 6/2A Ex BG	4044211199777	100

##INVERSE##CONTA-CONNECT



