



**CRYSTEK**  
**MICROWAVE**  
 A DIVISION OF CRYSTEK CORPORATION

**RG58A/U N-TYPE  
 RF COAX CABLE ASSEMBLIES**



RG58A/U 50 ohms  
 N-Type Coaxial Cable Assemblies



**Features:**

- Strain Relief:** Adhesive shrink tubing over crimp area
- Center Conductor:** TPC (Tin-Plated Copper) 19/0072
- Shielding:** TPC (Tin-Plated Copper) 96% Coverage, Single Braid
- Dielectric:** Solid Polyethylene
- Jacket:** PVC (Polyvinyl Chloride) Black
- Operating Temperature:** -40°C to +80°C
- Minimum Bend Radius:** 1.0"

Part Number	Description	Length
CCN-MM-RG58-12	RG58A/U Shielded Cable, N-Type Male/Male	12"
CCN-MM-RG58-24	RG58A/U Shielded Cable, N-Type Male/Male	24"
CCN-MM-RG58-36	RG58A/U Shielded Cable, N-Type Male/Male	36"



**CRYSTEK**  
 CORPORATION

12730 COMMONWEALTH DRIVE • FORT MYERS, FL 33913  
 PHONE: 239-561-3311 • 800-237-3061  
 FAX: 239-561-1025 • WWW.CRYSTEK.COM

Rev.: B  
 Date: 04-07-14