



DIMENSIONS SHOWN ARE REFERENCE ONLY

NOTES:

1. MEETS SMPTE 2082-1
CHARACTERISTIC IMPEDANCE :75 OHMS
CONTACT RESISTANCE: 50 MILLIOHMS MAX.
2. WIRING: CENTER CONTACT TO CENTER CONTACTS
GROUND SLEEVE TO GROUND SLEEVE
3. MATERIAL:
PLUG: COPPER ALLOY, NICKEL PLATED.
CONTACT: COPPER ALLOY, GOLD PLATED.
INSULATOR: TEFLON
CABLE: SILVER PLATED CONDUCTOR, COPPER/TIN SHIELD.
OVERMOLD: THERMOPLASTIC ELASTOMER
4. THIS PRODUCT IS RoHS COMPLIANT.

CUSTOMER DRAWING

					<div>UNLESS OTHERWISE SPECIFIED</div> <div>1. ALL DIMENSIONS IN INCHES [mm]</div> <div>- TWO PLACE DECIMALS ±0.02 [0.5]</div> <div>- THREE PLACE DECIMALS ±0.005 [0.13]</div>	THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.										
						SIZE	WIDTH		MULT		LBS/M		TEMPER			
						FINISH SPEC No.					MATERIAL SPEC No.					
						FIRST USED ON				SCALE 3:2		<div>Switchcraft®</div>				
						DATE DRAWN	BY	CHKD		APVD						
						5/01/17	PNK	PNK 5/01/17		SRC 5/01/17						
0A	PDR 16006	5/01/17	PNK	SRC												
REV	ECO NUMBER	DATE	BY	APVD												
REVISIONS					DO NOT SCALE DRAWING	NAME LOOPING PLUG UHD MICRO, OVERMOLDED, RoHS					PART No. VMMLPUHD			REV 0A		