

G2-ROSE-UV-W

~40° wide beam. Assembly black holder and installation tape.

SPECIFICATION:

Dimensions	21.6 x 21.6 mm
Height	12.9 mm
Fastening	tape, pin
ROHS compliant	yes ⓘ




MATERIALS:

Component	Type	Material	Colour	Finish
G2-ROSE-UV-W	Single lens	Silicone	clear	
G2-ROSE-LT-HLD	Holder	PC	black	
ROSE-TAPE	Tape	Acrylic foam	black	






ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
FCA15009_G2-ROSE-UV-W	Single lens	1620	360	180	6.6
» Box size: 480 x 280 x 165 mm					



See also our general installation guide: www.ledil.com/installation_guide








OPTICAL RESULTS (MEASURED):

	
LED	LZ1-00UV00
FWHM / FWTM	44.0° / 80.0°
Efficiency	%
LEDs/each optic	1
Light colour	UV-A
Required components:	
	
LED	LZ4-04UV00
FWHM / FWTM	36.0° / 80.0°
Efficiency	%
LEDs/each optic	1
Light colour	UV-A
Required components:	
	
LED	SST-10-B130
FWHM / FWTM	26.0° / 80.0°
Efficiency	%
LEDs/each optic	1
Light colour	UV-A
Required components:	
	
LED	NVSU233A
FWHM / FWTM	47.0° / 82.0°
Efficiency	%
LEDs/each optic	1
Light colour	UV-A
Required components:	
	





OPTICAL RESULTS (MEASURED):



OPTICAL RESULTS (SIMULATED):

<p>LUMINUS</p> <p>LED: SBT-10X-UV FWHM / FWTM: 72.0° / 98.0° Efficiency: 93 % LEDs/each optic: 1 Light colour: UV-A Required components:</p>	<p>Polar intensity graph</p> 	
<p>LUMINUS</p> <p>LED: SST-08-UV-A40 FWHM / FWTM: 33.0° / 57.0° Efficiency: 85 % LEDs/each optic: 1 Light colour: UV-A Required components:</p>	<p>Polar intensity graph</p> 	
<p>LUMINUS</p> <p>LED: SST-10-A130 FWHM / FWTM: 21.0° / 77.0° Efficiency: 85 % LEDs/each optic: 1 Light colour: UV-A Required components:</p>		
<p>NICHIA</p> <p>LED: NVSU233A FWHM / FWTM: 44.0° / 65.0° Efficiency: 90 % Peak intensity: 1.8 cd/lm LEDs/each optic: 1 Light colour: UV-A Required components:</p>		

OPTICAL RESULTS (SIMULATED):

<p>NICHIA</p> <p>LED: NVSxx19B/NVSxx19C FWHM / FWTM: 32.0° / 80.0° Efficiency: 84 % Peak intensity: 1.7 cd/lm LEDs/each optic: 1 Light colour: UV-A Required components:</p>		
<p>SEOUL SEMICONDUCTOR</p> <p>LED: CUN66B1G FWHM / FWTM: 32.0° / 69.0° Efficiency: 74 % LEDs/each optic: 1 Light colour: UV-A Required components:</p>		
<p>STANLEY</p> <p>LED: LZU4E FWHM / FWTM: 18.0° / 70.0° Efficiency: 84 % LEDs/each optic: 1 Light colour: UV-A Required components:</p>	<p>Polar intensity graph</p> 	

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)