

Eco-Surge 7-Outlet, Surge Protector, 4-ft Cord, 1400 Joules, Timer-Controlled

MODEL NUMBER: TLP74TG



Highlights

- Timer-controlled outlets
- Two separate outlet banks
- 1400 joules
- 7 outlet / 4-ft cord
- Diagnostic LEDs

Package Includes

- TLP74TG ECO-SURGE Home/Business Theater Surge Suppressor
- Instruction manual with warranty information

Description

Tripp Lite's TLP74TG offers reliable, GREEN surge technology that protects your computer and peripherals as well as the environment and your wallet. Energy-saving outlet configuration reduces energy waste (phantom loads) by cutting AC power to unused peripherals. Convenient, multiple programmable timers allow users to set the exact time a device is turned on and off. The unit has 2 separate banks of outlets so you can program up to 20 timer options. The TLP74TG has 7 total outlets, 4 foot cord and diagnostic LEDs to warn of wiring problems and suppressor damage. Network-grade AC suppression rated at 1400 joules shields equipment from surges and line noise. Designed with an attractive cool gray suppressor housing, the TLP74TG provides 1 designated transformer outlet but can accommodate up to 4 transformer plug outlets offering convenient protection of desktop computer equipment and accessories. \$75,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

Features

- Energy-saving outlet configuration reduces energy waste (phantom loads) by cutting AC power to unused peripherals
- Programmable timer controls the output based on user settings. The timer can be set to automatically power connected ON and OFF based on time of day and day of the week for up to 20 possible timer settings.
- Two sets of timer-controlled outlet banks allow the user to connect equipment with varying timer settings.
- 1400 joules surge suppression rating with EMI/RFI line noise filtering help components perform at their peak (sharper, crisper video; deeper, fuller audio and longer component life spans)
- 7 surge-protected NEMA 5-15R AC outlets safeguard and entire home/business theater system while accommodating up to 4 large transformers
- 2 diagnostic LEDs alert user to protection and grounded status
- Lighted on/off switch with integrated circuit breaker - protects against dangerous system overload
- \$75,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)
- Automatic shutoff cuts power to outlets when the protection circuit has been compromised



Specifications

| OVERVIEW | |
|------------------------------------|---|
| UPC Code | 037332161352 |
| INPUT | |
| Nominal Input Voltage(s) Supported | 120V AC |
| Recommended Electrical Service | 120V (110-125V) |
| Input Cord Gauge Type | 14 gauge; SJT |
| Voltage Compatibility (VAC) | 120 |
| Maximum Surge Amps | 19500 |
| Input Plug Type | NEMA 5-15P |
| Input Cord Length (ft.) | 4 |
| Right-Angle Plug | No |
| Input Cord Length (m) | 1.22 |
| Integrated Cord Clip | No |
| OUTPUT | |
| Output Volt Amp Capacity (VA) | 15 |
| Output Watt Capacity (Watts) | 1875 |
| Frequency Compatibility | 60 Hz |
| Output (Watts) | 1800 |
| Output Receptacles | (7) 5-15R |
| Transformer Accommodation | (4) Yes |
| Right-Angle Outlets | No |
| USER INTERFACE, ALERTS & CONTROLS | |
| Diagnostic LED(s) | Yes |
| Front Panel LCD Display | AM/PM LCD Clock |
| Switches | Combination AC circuit breaker and 2 position lighted on/off power switch |
| LED Indicators | Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status |
| SURGE / NOISE SUPPRESSION | |
| AC Suppression Joule Rating | 1400 |
| AC Suppression Response Time | < 1 ns |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| | |
|--|--|
| Protection Modes | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression. |
| UL1449 Let Through Rating | 400 |
| EMI / RFI Filtering | Up to 20 dB |
| Automatic Shut-Off | Yes |
| DATALINE SURGE SUPPRESSION | |
| Cable (Coax) Protection | No |
| Network (Ethernet) Protection | No |
| Telephone/DSL Protection | No |
| PHYSICAL | |
| Material of Construction | plastic |
| Color | Gray |
| Power Cord Color | Gray |
| Housing Color | Gray |
| Mounting Holes or Slots | No |
| Outlets Measurement (Center to Center) | Distance between standard outlets = 28.5mm; Distance between standard outlet and transformer outlet = 57mm |
| Receptacle Color | Gray |
| Shipping Dimensions (hwd / cm) | 34.80 x 5.59 x 14.48 |
| Shipping Dimensions (hwd / in.) | 13.70 x 2.20 x 5.70 |
| Shipping Weight (kg) | 0.68 |
| Shipping Weight (lbs.) | 1.50 |
| Unit Dimensions (hwd / in.) | 1.56 x 3.54 x 11.22 |
| Unit Dimensions (hwd / cm) | 3.96 x 8.99 x 28.50 |
| Unit Weight (lbs.) | 1.43 |
| Unit Weight (kg) | 0.65 |
| FEATURES & SPECIFICATIONS | |
| Green Energy-Saving Features | Schedulable daily hours of economy mode operation |
| Antimicrobial | No |
| Rotatable Outlets | No |
| WARRANTY | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$75,000 Ultimate Lifetime Insurance |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:
<https://www.tripplite.com/products/product-certification-agencies>