

Specification Sheet

Part Number: S2CM258HIRHSH1

Separates bundles from wear and chafing, providing additional longevity. Hexagonal retention feature (S2HM25) captures a bolt or nut requiring tool access from the back side only.

A socket counterbore allows securing with a socket wrench from the top side for use with a weld stud or bolt (S2CM25.)

Made from impact modified, heat stabilized, UV resistant material making it ideal for heavy duty applications.



2-Way Saddle Mount, 3.5" Max Bundle Diameter, 0.25" Stud Diameter, PA66HIRHS, Gray, 500/pkg

Article Number 151-29400

Type S2CM25

Color Gray (GY)

Quantity Per bag

Product Description HellermannTyton's saddle mount can be installed between two bundles (such as wires, cables, hoses, tubing, conduit, etc.) to separate them and prevent chafing and wear. Fastened to a frame rail or mounting bracket, the H-profile on the saddle mount provides a tight circumferential loop on large and small bundles. Cable ties up to 1/2" wide are used to secure the bundles.

Short Description	2-Way Saddle Mount, 3.5" Max Bundle Diameter, 0.25" Stud Diameter, PA66HIRHS, Gray, 500/pkg
Global Part Name	S2CM25-PA66HIRHS-GY
Length L (Imperial)	1.80
Length L (Metric)	45.0
Fixation Method	Screw Mounting and Rivet
Width W (Imperial)	1.2
Width W (Metric)	30.0
Bundle Diameter Max (Imperial)	3.5
Bundle Diameter Max (Metric)	89.0
Cable Ties	T50 - T250
Height H (Imperial)	0.90
Height H (Metric)	23.0
Cable Tie Width Max (Imperial)	0.53
Cable Tie Width Max (Metric)	13.5
Mounting Hole Diameter D (Imperial)	0.24
Mounting Hole Diameter D (Metric)	6.0 mm 6.35 mm (hexagonal)

Mounting Hole Diameter D Min (Imperial) 0.24

Mounting Hole Diameter D Max (Imperial) 0.24

Mounting Hole Diameter D Max (Metric) 6.0

Stud Diameter (Metric) 6.35 mm

Stud Diameter (Imperial) 0.25

Material Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Material Shortcut PA66HIRHS

Flammability UL 94 HB

UV Resistant (Yes/No) No

Operating Temperature -40°F to +230°F (-40°C to +110°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)