

FO patch cable - FL MM PATCH 5,0 LC-SC - 2901800

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Assembled FO cable, break out cable, multi-mode fiberglass 50/125 µm, plug: LC / SC-Duplex, protection type: IP20, for installation in cable ducts or control cabinets, length: 5 m



Key commercial data

| | |
|--------------------------------------|-----------|
| Packing unit | 1 pc |
| Weight per Piece (excluding packing) | 100.0 GRM |
| Custom tariff number | 85447000 |
| Country of origin | Germany |

Technical data

Cable type

| | |
|------------|----------------------|
| Cable type | Multimode fiberglass |
|------------|----------------------|

Ambient conditions

| | |
|---|---|
| Ambient temperature (operation) | -5 °C ... 70 °C |
| Ambient temperature (storage/transport) | -25 °C ... 70 °C |
| Ambient temperature (installation) | -5 °C ... 50 °C |
| Resistance to oil | Not resistant to oil, gasoline, acids, and lyes |

External sheath

| | |
|---|-----------------------------|
| Outer sheath, material | FRNC |
| External sheath, color | orange |
| External sheath, strain relief elements | Non-metallic, aramide fiber |
| External diameter max. | 5.7 mm |

Single wire

| | |
|-----------------------------|--------|
| Individual wires per module | 2 |
| Individual wire, diameter | 2.8 mm |

FO patch cable - FL MM PATCH 5,0 LC-SC - 2901800

Technical data

Mechanical properties

| | |
|---------------------------------------|-----------|
| Bending radius short term/long term | 30 mm |
| Bending radius, long-term | 60 mm |
| Lateral pressure, long-term | 60 N/cm |
| Tensile strength short-term/long-term | 600 N |
| Cable, attenuation | 2.5 dB/km |
| | 0.7 dB/km |

General

| | |
|---|------------|
| Cable weight | 15.8 kg/km |
| Transmission characteristics (category) | OM2 |
| Transmission speed | 1 Gbps |

Behavior in fire

| | |
|------------------------|------------------------------|
| Flame resistance | According to DIN 60332-1-2 |
| | IEC 60332-3-22 (Cat. A) |
| Concentration of fumes | in accordance with IEC 61034 |
| Halogen-free | According to IEC 60754-2 |
| Behavior in fire | No corrosive or toxic fumes |
| | 0.36 MJ/m |

Attenuation

| | |
|---------|-----------|
| 850 nm | 2.5 dB/km |
| 1300 nm | 0.7 dB/km |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27061003 |
| eCl@ss 5.0 | 27061003 |
| eCl@ss 5.1 | 27061003 |
| eCl@ss 6.0 | 27259207 |
| eCl@ss 7.0 | 27259207 |
| eCl@ss 8.0 | 27061003 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000034 |
| ETIM 3.0 | EC000034 |
| ETIM 4.0 | EC000034 |

FO patch cable - FL MM PATCH 5,0 LC-SC - 2901800

Classifications

ETIM

| | |
|----------|----------|
| ETIM 5.0 | EC001263 |
|----------|----------|

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 26121607 |
| UNSPSC 7.0901 | 26121607 |
| UNSPSC 11 | 26121607 |
| UNSPSC 12.01 | 26121607 |
| UNSPSC 13.2 | 26121607 |

Drawings

Catalog photo



Figure may contain other products.