

# XUYFVERSD101

Photoelectric sensors XU, glass fibre optic for sensor, thru beam, straight, standard, 1 m, Sn200mm



## Main

|                               |  |
|-------------------------------|--|
| Range of Product              | Telemecanique Photoelectric sensors XU |
| Sensor name                   | XUY                                    |
| Sensor design                 | Fiber design                           |
| Sheath type                   | Standard                               |
| [Sn] nominal sensing distance | 7.87 in (200 mm) XUYAFV                |
| End fitting type              | Straight nickel plated brass, M4 x 0.7 |

## Complementary

|                        |                          |
|------------------------|--------------------------|
| Electronic sensor type | Photo-electric sensor    |
| Optic fiber material   | 50 μ glass               |
| Sheath material        | PVC + thermo polyolefine |
| Detection system       | Thru beam                |
| Optic fiber length     | 3.28 ft (1 m)            |
| Minimum bending radius | 0.39 in (10 mm)          |
| Head mounting          | M4 x 0.7                 |
| Net Weight             | 0.09 lb(US) (0.042 kg)   |

## Environment

|                                       |                            |
|---------------------------------------|----------------------------|
| Ambient Air Temperature for Operation | -13...140 °F (-25...60 °C) |
|---------------------------------------|----------------------------|

## Ordering and shipping details

|                       |                              |
|-----------------------|------------------------------|
| Category              | 22481-SENSORS, PHOTOELECTRIC |
| Discount Schedule     | DS2                          |
| GTIN                  | 3389119008037                |
| Nbr. of units in pkg. | 1                            |
| Package weight(Lbs)   | 1.83 oz (52.0 g)             |
| Returnability         | No                           |
| Country of origin     | FR                           |

## Packing Units

|                              |                        |
|------------------------------|------------------------|
| Unit Type of Package 1       | PCE                    |
| Package 1 Height             | 0.59 in (1.5 cm)       |
| Package 1 width              | 5.12 in (13 cm)        |
| Package 1 Length             | 5.35 in (13.6 cm)      |
| Unit Type of Package 2       | S01                    |
| Number of Units in Package 2 | 25                     |
| Package 2 Weight             | 3.18 lb(US) (1.443 kg) |
| Package 2 Height             | 5.91 in (15 cm)        |
| Package 2 width              | 5.91 in (15 cm)        |
| Package 2 Length             | 15.75 in (40 cm)       |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| California proposition 65  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           |  <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)  <a href="#">EU RoHS Declaration</a>  |
| Mercury free               | Yes   |
| RoHS exemption information |  <a href="#">Yes</a>   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|