



Siemens Low Voltage Circuit Protection Heavy Duty Safety Switches. Type: ENCLOSED, SAFETY SWITCH Std: UL V. Rating: 600V A. Rating: 200A Wattage: 3W No. Of Poles: 3P F. Rating: 60Hz Action: DOUBLE THROW Material: SS Enclosure: TYPE 4X. 2-3 point mounting holes. Insulation: YES O. Cycles: 8000 O. Temperature: (-20F-120F) AMBIENT TEMPERATURE Environmental Conditions: INDUSTRIAL CORROSIVE RESISTANCE

|  |                                     |
|--|-------------------------------------|
| mechanical service life (switching cycles) typical | 8000                                |
| fastening method                                   | SURFACE                             |
| number of poles                                    | 3                                   |
| suitability for operation                          | LOAD TRANSFER BETWEEN POWER SOURCES |
| <b>Electricity</b>                                 |                                     |
| ampacity   | 200 A                               |
| supply voltage frequency rated value 50/60 Hz      | Yes                                 |
| <b>Model</b>                                       |                                     |
| product brand name                                 | SIEMENS                             |
| product type designation                           | DOUBLE THROW SWITCH                 |
| type of electrical connection                      | MECHANICAL LUGS                     |
| <b>Mechanical Design</b>                           |                                     |
| design of the housing                              | TYPE 4X                             |
| design of the actuating element                    | DOUBLE THROW                        |
| material   | 304 STAINLESS STEEL                 |
| <b>General product approval</b>                    |                                     |
| certificate of suitability                         | UL98                                |

last modified: 9/16/2021 

