

Insert Strips for Cable Marker (KMK...), Terminal Strip Marker (KLM...) and Terminal Strip Label (UBE...)

1. Description

Nowadays, the demands made of marking with respect to durability and appearance are ever increasing. To meet these requirements, we now supply two new options made of a perforated plastic foil (see photo). They can be labeled using a conventional laser printer (DIN A 4 format), or a thermo transfer printer (for material off the roll). It is of course still possible to label them with the M-PEN or CMS plotter. The advantages are that the lettering is permanent and makes an excellent impression, it is resistant to solvents, simple to handle and saves time when you have a greater throughput.









EST...

ESL...

Insert strips, can be labeled with thermo transfer printer

Insert strips, can be labeled with laser printer

2. Technical Data

Insert strip, can be labeled with the thermo transfer printer ¹)

2.1. Description Insert strip, for KLM 1, LM and AK-DST-UK, marking area 24 x 4 mm, white 1 roll = 5.000 marker labels Insert strip, for KMK and KMK 2, marking area 29 x 8 mm, white 1 roll = 5.400 marker labels Insert strip, for KMK 3, KMK 4 and UBE, UBE/D, white marking area 40 x 17 mm, 1 roll = 2.300 marker labels Insert strip, for KLM, marking area 25 x 6 mm, white 1 roll = 5.000 marker labels Large format insert strip, can be labeled with the laser printer ²) 2.2. Description Large format insert strip, perforated, DIN A 4, for KLM 1, LM and AK-DST-UK, 488-section white marking area 24 x 4 mm Large format insert strip, perforated, DIN A 4, for KMK and KMK 2, 174-section white marking area 29 x 8 mm Large format insert strip, perforated, DIN A 4, for KMK 3, KMK 4 and UBE, UBE/D, marking area 40 x 17 mm 56-section white Large format insert strip, perforated, DIN A 4, 266-section 26 x 6 mm 266-section white Large format insert strip, perforated, DIN A 4, for KLM-A, marking area 44 x 7 mm 136-section white 2.3. General Data EST... Material Temperature range [°C] ESL... Material

[°C]

Туре	Order No.	<u>Pcs.</u> Pkt.
EST 24 x 4	08 09 27 2	1
EST 29 x 8	08 07 46 5	1
EST 40 x 17	08 07 48 1	1
EST 25 x 6	08 07 47 8	1
Туре	Order No.	<u>Pcs.</u> Pkt.
ESL 24 x 4	08 08 23 1	10
ESL 29 x 8	08 08 25 7	10
ESL 40 x 17	08 08 09 5	10
ESL 26 x 6	08 08 10 5	10
ESL 44 x 7	08 08 24 4	10
	·	
polyethylene – 40 to + 100		

Temperature range

¹) For further information, see Catalog CLIPLINE. ²) Should you require more information, we would be pleased to be of assistance.

Phoenix Contact page 2 of 2