

EXPLODED VIEW NOT TO SCALE (FOR CLARITY ONLY)

NOTES:

BODY, CLAMP NUT, OUTER CONTACT: STAINLESS STEEL. O-RING: SILICONE RUBBER.

BEAD: ULTEM.

SOLDER FERRULE: BRASS ALLOY CONTACT: BERYLLIUM COPPER.

2. FINISH:

BODY, CLAMP NUT, OUTER CONTACT: PASSIVATED. CONTACT, SOLDER FERRULE: GOLD OVER NICKEL PLATE, 50 µIN MIN GOLD OVER 50 µIN MIN NICKEL.

3. PCI P/N: 3176.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. TOLERANCES ARE:

DECIMALS **ANGLES** .XX: ±.01

.XXX: ±.005 .XXXX: ±.0005

PROPRIETARY NOTE THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND ALL DESIGN, MANUFACTURING, REPRODUCTION, USE, PATENT RIGHTS AND SALES RIGHTS ARE EXPRESSLY RESERVED BY SAMTEC, INC. THIS DOCUMENT SHALL NOT BE DISCLOSED, IN WHOLE OR PART, TO ANY UNAUTHORIZED PERSON OR ENTITY NOR REPRODUCED, TRANSFERRED OR INCORPORATED IN ANY OTHER PROJECT IN ANY MANNER WITHOUT THE EXPRESS

WRITTEN CONSENT OF SAMTEC INC

DO NOT SCALE DRAWING

SHEET SCALE: 3:1


PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail info@SAMTEC.com code 55322

2.4MM JACK ASSEMBLY FOR DESCRIPTION: **INSULATED WIRE 1401**

DWG. NO. PRF24-J-C-EP-140B-SS


BY: CANDY W 05/16/2019 | SHEET 1 OF 2

F:\dwg\misc\mktg\PRF24-J-C-EP-140B-SS-MKT.SLDDRW




1. TRIM CABLE AND POINT CENTER CONDUCTOR AS SHOWN.

IN-PROCESS VIEW 1



- 2A. SLIDE CLAMP NUT OVER CABLE AS SHOWN.
- 2B. INSERT CABLE INTO SOLDER FERRULE UNTIL SEATED AND SOLDER TO CABLE BRAID & FOIL.

IN-PROCESS VIEW 2



3A. INSERT CABLE/FERRULE SUB-ASSEMBLY INTO CONNECTOR UNTIL SEATED AND TIGHTEN CLAMP NUT TO 25-35 IN-LBS.

3B. GAGE INTERFACE USING APPROPRIATE GAGE (CONTACT RANGE 000/.003 SUB-FLUSH).

* PROPRIETARY NOTE THIS DOCUMENT CONTAINS CONFIDENTIAL AND

PROPRIETARY INFORMATION AND ALL DESIGN,
MANUFACTURING, PERPODUCTION, USE PATENT RIGHTS
AND SALES RIGHTS ARE SERVESSAY RESERVED BY SAMFE,
INC. THIS DOCUMENT SHAPE IN EXCLUSED, BY MEY,
OR PART, TO ANY UNAUTHORIZED PRESON OR ENTITY NOR
PERPODUCED, TRANSFERRED OR HOROPRORATE ID INVO
OTHER PROJECT IN ANY MANNER WITHOUT THE EXPRESS
WRITTEN CONSENT OF SAMFE, IS

DO NOT SCALE DRAWING

SHEET SCALE: 3:1

<u>sam(ec</u>

520 PARK EAST BLVD, NEW ALBANY, IN 47150 PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail info@SAMTEC.com code 55322

DESCRIPTION: 2.4

2.4MM JACK ASSEMBLY FOR INSULATED WIRE 1401

DWG. NO.

PRF24-J-C-EP-140B-SS

BY: CANDY W 05/16/2019 SHEET 2 OF 2

1 K1 24-J-C-L1 -140D-3

DISTANCE FROM END OF CABLE CENTER COND. TO REF. PL. IS .275 (REF.)

F:\dwg\misc\mktg\PRF24-J-C-EP-140B-SS-MKT.SLDDRW

IN-PROCESS VIEW 3