



Fused Terminal Blocks

1003 SI/ 1 DS GW

screw terminal block with fuse holder 6,3x25/6,3x32, 1 pole, wire protector (DS): yes, cross-section rating: 4.0 mm², voltage rating: 500 V, current rating: 16 A



Order Info

reference number (ref.no.)	11618
PU	100
EAN	4028012143993

Type

type	screw terminal block with fuse holder 6,3x25/6,3x32
number of poles	1 pole
clamping units per pole	1
cross-section rating	4.0 mm ²
connection type	screw
wire protector (DS)	yes

Technical Data

voltage rating	500 V
current rating	16 A
insulating material	PA GW
contact material	brass
core cross-section min.	0.5 mm ²
core cross-section max.	4.0 mm ²
flammability rating	V-2
min. ambient temperature	-40 °C
max. ambient temperature operation	85 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	7.5-8.0 mm
assembly contact screw	0.8x4.0 / ⚙ 0.8 Nm
type of conductor solid external	yes
type of conductor flexibel external	yes
type of conductor stranded external	yes
type of conductor solid internal	yes
type of conductor stranded internal	yes

type of conductor flexible internal yes

Approvals

acc. to EN 60127 [Download PDF](#)

acc. to UL [Download PDF](#)

acc. to CSA [Download PDF](#)
